EQUIPMENT PRICING TEMPLATE RFP #17-CNPKFL-0424

Vendor All Specification are provided on manufacturer description. The awarded vendor is responsible to ensure that equipment meets Information the space needs of the identified campus.

Vendor Quote Submittal

| | IDEA Donna - 401 | S 1st St Donna | TY 7853 | | | | |
|------|---|----------------|---------|-------|-------------------|------------|--------------|
| Item | Description | | 17.7000 | | Installation Cost | | |
| | Description | Requested | Brand | Price | | Total Cost | Vendor Notes |
| | | Quantity | | | Per Unit | | |
| 1 | Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per | 3 | | | | | |
| | plans, elevations and manufacturer's specifications | | | | | | |
| | Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer | | | | | | |
| | Cover to be stainless steel and hinged with condensate ring | | | | | | |
| | Power pan tilt, tilting console with provision for faucet | | | | | | |
| | Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition | | | | | | |
| | • Each unit to be 480V, 3 phase, 60 Hz, 12kw | | | | | | |
| | One Year parts and labor warranty | | | | | | |
| | • (2) Faucet bracket assembly | | | | | | |
| | • (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer | | | | | | |
| | • (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) | | | | | | |
| | • (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit) | | | | | | |
| 2 | Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place | 4 | | | | | |
| _ | per plans, elevations and manufacturer's specifications. | | | | | | |
| | Provide Blodgett full size convection oven model Mark V (double) compartment. | | | | | | |
| | Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans. | | | | | | |
| | • Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous | | | | | | |
| | operation. | | | | | | |
| | Unit to be electrically heated with three tubular heaters. | | | | | | |
| | Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload | | | | | | |
| | protection. | | | | | | |
| | Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. | | | | | | |
| | • Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200-500 degrees) with 60 | | | | | | |
| | minute timer. | | | | | | |
| | Equip units with all standard features available on these units. | | | | | | |
| | Double-Deck | | | | | | |
| | Provide all stainless steel 8" legs. | | | | | | |
| | Provide vent connector. | | | | | | |
| | Warranty; provide Five year limited oven door warranty. | | | | | | |
| | One-year parts and labor warranty. | | | | | | |
| | Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total | | | | | | |
| 3 | 3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate | 1 | | | | | |
| | Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" | | | | | | |
| | front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable | | | | | | |
| | left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel, | | | | | | |
| | overall 31" F/B x 151" L/R, NSF | | | | | | |
| | (requires 2 faucets) | | | | | | |
| | 1 ea K-453 Control Bracket, 14" x 16" (each) | | | | | | |
| | 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections | | | | | | |
| | 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain | | | | | | |
| 4 | Pre-Rinse Faucet assembly with add on faucet | 1 | | | | | |
| 5 | Wall / Splash mount faucet | 1 | | | | | |
| 6 | Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 | 1 | | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications. | | | | | | |
| | Water Filtration System Cartridge for Premium Quality Water | | | | | | |
| | • 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing | | | | | | |
| | • 12 gallon capacity | | | | | | |
| | NEMA L6-30P Locking Cap in lieu of NEMA 6-30P | | | | | | |
| | • 208V, 1 phase 60 Hz, 24.0A | | | | | | |

| 7 | Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate. | 1 | | | |
|------|---|---|--|---|--|
| | Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length. | | | | |
| | • Sink to be 18" x 24" with 18" drainboards each side. | | | | |
| | Wash sink compartment to be 11-1/2" deep with 11"H backsplash | | | | |
| | | | | | |
| | • Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, | | | | |
| | wall bracket. | | | | |
| | Add-On-Faucet with 12" swing spout | | | | |
| 8 | Pre-Rinse Faucet assembly with add on faucet | 1 | | | |
| 9 | Ice Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice | 1 | | | |
| | Maker, cube-style, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes | | | | |
| | (not stackable). | | | | |
| | Refer to MEP for connections | | | | |
| | | | | | |
| | • 3 year parts & labor warranty | | | | |
| | • 5 year parts & labor warranty on evaporator | | | | |
| | 5- year parts & 3- year labor warranty on compressor | | | | |
| | Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter | | | | |
| | cartridge, (NOT stand-alone; should be used in conjunction with primary water filter assembly) | | | | |
| | • Ice Bin, 48"W x 34"D, 50"H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice | | | | |
| | maker, stainless steel exterior, NSF | | | | |
| | • 6" adjustable stainless steel legs, std. | | | | |
| 10 | Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart | 1 | | | |
| 1 10 | | 1 | | | |
| 1 | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | |
| | • 30"x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| | 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | |
| | Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | |
| | | | | | |
| 11 | Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E | 1 | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | |
| | • Power; 120v,60Hz, 7.6 A. | | | | |
| 12 | Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table | 1 | | | |
| 12 | · · · | 1 | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | |
| | • Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and | | | | |
| | under shelf. | | | | |
| | TA-366 Reinforced understructure for undershelves (maximum | | | | |
| | recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| | • SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, | | | | |
| | stainless steel, with drawer slides | | | | |
| | Provide with 1-1/2" backsplash | | | | |
| 13 | Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack Furnish and | 1 | | | |
| 13 | set in place per plans, elevations and manufacturer's specifications | - | | | |
| | | | | | |
| | • Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf. | | | | |
| | Provide table with one (1) pot rack to be center-mounted to table | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| | 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | |
| | Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | |
| | | | | | |
| 14 | Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table | 1 | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | |
| | • Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and | | | | |
| 1 | under shelf. | | | | |
| 1 | | | | | |
| 1 | Provide One (1) Edlund can opener and mount to table per drawing. Printed and address the form death has form death has form death and 20 lbs are as form and distributed as left. | | | | |
| 1 | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| | 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | |
| 1 | • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | |
| | | | | | |
| 15 | Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table | 4 | | | |
| 1 | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | |
| | Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs | | | | |
| 1 | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| 1 | • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | |
| | • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | |
| 1 | - 2 Delune Drawers, 13 W X 20 D X 3 Geep Grawer pair insert, staffiness steer, with Grawer Silves | | | | |
| 10 | Mahila Dan Dadi. Manufashurar (Madali Nau Asa Industrial Cost. No. 2022440 | 4 | | | |
| 16 | Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 | 1 | | | |
| 1 | Furnish and set in place per plans, elevations and manufacturer's specifications | | | 1 | |

| 17 | Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal | 3 | | | | |
|----|--|----|---|---|---|---|
| | Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip | | | | | |
| | with hardware, stainless steel | | | | | |
| | Faucet, splash type, rigid gooseneck, with standard handles | | | | | |
| | | | | | | |
| | Foot Pedal Valve | | | | | |
| | Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts | | | | | |
| | • P Trap | | | | | |
| 18 | Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications | 4 | | | | |
| 19 | Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per pla | 10 | | | | |
| 20 | Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate | 6 | | | | |
| | Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full- | | | | | |
| | height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF, | | | | | |
| | Refer to MEP for connections | | | | | |
| | • 1 yr service/labor, 3 yr parts & warranty, standard | | | | | |
| | | | | | | |
| | Thermometer side: Door hinging to be determined | | | | | |
| | Rear: Door hinging to be determined | | | | | |
| | • 208V, 1P, 60hz | | | | | |
| | Provide New Age 4338 Roll-in Rack at each unit. | | | | | |
| 21 | Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate | 4 | | | | |
| | Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full- | | | | | |
| | height doors, INTELA-TRAUL™ microprocessor controls. | | | | | |
| | Refer to MEP for connections | | | | | |
| | • 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard | | | | | |
| | Thermometer side: Door hinging to be determined | | | | | |
| | Rear: Door hinging to be determined | | | | | |
| | | | | | | |
| | • 120V , 1P, 60hz | | | | | |
| | Provide New Age 4338 Roll-in Rack at each unit. | | | | | |
| 22 | Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate | 2 | | | | |
| | CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with | | | | | |
| | integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz | | | | | |
| | CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable | | | | | |
| | Deluxe sneeze guard with glass overshelf and lights. 120V/1P/60hz | | | | | |
| | CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide | | | | | |
| | unit with grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated | | | | | |
| | decor panels with cord/plug. | | | | | |
| | | | | | | |
| 27 | Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP | 1 | | | | |
| | 16" shaft, Heavy Duty; Variable speed | _ | | | | |
| | Power- 120V; 60 Hz; 6.2 Amps | | | | | |
| | · · · · | | | | | |
| 28 | This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. | | | | | |
| 28 | Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender | 1 | | | | |
| | Ultra-heavy-duty, 3.75 HP commercial motor | | | | | |
| | 3-speed selection and MAX PULSE to chop and mix | | | | | |
| | Durable, full die-cast motor housing with rugged | | | | | |
| | rubber feet to reduce vibration | | | | | |
| | Power- 120V; 60Hz; 15 Amps | | | | | |
| 29 | Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS | 1 | | | | |
| | Furnish and place per plans | | | | | |
| | Commercial microwave 10 touch pad control panel shall be | | | | | |
| 1 | programmable with the ability to program up to 100 menu | | | | | |
| 1 | items with two multiple portions. Touch pad shall include | | | | | |
| 1 | Braille for ADA compliance. Cooking timer shall be 60 minute, | | | | | |
| 1 | countdown style with a time entry option and an adjustable | | | | | |
| 1 | | | | | | |
| | end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall | | | | | |
| | be 1000 watts distributed by one magnetron with a rotating | | | | | |
| | top antenna to provide superior even heating throughout the | | | | | |
| | cavity. Durable door shall have a tempered glass window and | | | | | |
| | a grab and go handle with a 90o | | | | | |
| | + opening for easy access. An | | | | | |
| 1 | interior light shall facilitate monitoring without opening the | | | | | |
| | door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate | | | | | |
| 1 | a 14" (356 mm) platter. | | | | | |
| | Power: 120V; 60Hz; 15 Amp | | | | | |
| | Install on a hanging shelf on an open space on the wall. | | | | | |
| L | material on a nongring shell on an open space on the wall. | | L | l | I | 1 |

| | 28 | Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with | 2 | | | |
|---|----|--|---|--|--|--|
| ı | | Clear Door - 120V or preapproval alternate | | | | |
| | 29 | Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right | 2 | | | |
| | | Hinge Solid Door, 115v or preapproval alternate | | | | |

Mobile Refrigerator (2) and mobile warmer (2) - Both should have sheet pan racks

| | IDEA Weslaco Pike - 1000 | 0 E Pike Blvd, We | slaco TX 78596 | | | | |
|------|--|-----------------------|----------------|-------|-------------------------------|------------|--------------|
| Item | Description | Requested Quantity | Brand | Price | Installation Cost Per Unit | Total Cost | Vendor Notes |
| 1 | Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans, elevations and manufacturer's specifications • Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer • Cover to be stainless steel and hinged with condensate ring • Power pan tilt, tilting console with provision for faucet • Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition • Each unit to be 480V, 3 phase, 60 Hz, 12kw • One Year parts and labor warranty • (2) Faucet bracket assembly • (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer • (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) • (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit) | 1 | | | | | |
| 2 | Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per plans, elevations and manufacturer's specifications. Provide Blodgett full size convection oven model Mark V (double) compartment. Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans. Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous operation. Unit to be electrically heated with three tubular heaters. Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload protection. Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60 minute timer. Equip units with all standard features available on these units. Double-Deck Provide all stainless steel 8" legs. Provide vent connector. Warranty; provide Five year limited oven door warranty. One-year parts and labor warranty. | 2 | | | | | |
| 3 | 3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF (requires 2 faucets) 1 ea K-453 Control Bracket, 14" x 16" (each) 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain | 1 | | | | | |
| 4 | Pre-Rinse Fauce assembly with add on faucet | 1 | | | | | |
| 5 | Wall / Splash mount faucet | 1 | | | | | |
| 6 | Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 Furnish and set in place per plans, elevations and manufacturer's specifications. • Water Filtration System Cartridge for Premium Quality Water • 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing • 12 gallon capacity • NEMA L6-30P Locking Cap in lieu of NEMA 6-30P • 208V, 1 phase 60 Hz, 24.0A | 0 | | | | | |

| 7 | Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate. | 1 | | | | |
|------|---|---|---|---|--------------|--------------|
| | Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length. | | | | | |
| | • Sink to be 18" x 24" with 18" drainboards each side. | | | | | |
| | | | | | | |
| | Wash sink compartment to be 11-1/2" deep with 11"H backsplash | | | | | |
| | • Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, | | | | | |
| | wall bracket. | | | | | |
| | Add-On-Faucet with 12" swing spout | | | | | |
| 8 | Pre-Rinse Fauce assembly with add on faucet | 1 | | | | |
| 9 | Ice Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice | 1 | | | | |
| 9 | | | | | | |
| | Maker, cube-style, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes | | | | | |
| | (not stackable). | | | | | |
| | Refer to MEP for connections | | | | | |
| | 3 year parts & labor warranty | | | | | |
| | • 5 year parts & labor warranty on evaporator | | | | | |
| | • 5- year parts & 3- year labor warranty on compressor | | | | | |
| | , | | | | | |
| | • Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter | | | | | |
| | cartridge, (NOT stand-alone; should be used in conjunction with primary water filter assembly) | | | | | |
| | • Ice Bin, 48"W x 34"D, 50"H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice | | | | | |
| | maker, stainless steel exterior, NSF | | | | | |
| | • 6" adjustable stainless steel legs, std. | | | | | |
| 10 | Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart | 1 | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | | |
| | • 30" x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf | | | | | |
| | | | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | | |
| | 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | | |
| | Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | | |
| | | | | | | |
| 11 | Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E | 1 | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | | |
| | • Power; 120v,60Hz, 7.6 A. | | | | | |
| 12 | Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table | 1 | | | | |
| 12 | , · | 1 | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | | |
| | • Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and | | | | | |
| | under shelf. | | | | | |
| | TA-366 Reinforced understructure for undershelves (maximum | | | | | |
| | recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | | |
| | • SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, | | | | | |
| | stainless steel, with drawer slides | | | | | |
| | • Provide with 1-1/2" backsplash | | | | | |
| 40 | | | | | | |
| 13 | Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack Furnish and | 1 | | | | |
| | set in place per plans, elevations and manufacturer's specifications | | | | | |
| | Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf. | | | | | |
| | Provide table with one (1) pot rack to be center-mounted to table | | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | | |
| | • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | | |
| | Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | | |
| | - betaze blawer, 15 W X20 B X3 deep drawer part insert, statiness steet, with drawer sinces | | | | | |
| 14 | Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table | 1 | 1 | + | | |
| 14 | | 1 | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | | |
| | • Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and | | | | | |
| | under shelf. | | | | | |
| | Provide One (1) Edlund can opener and mount to table per drawing. | | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | | |
| | 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | | |
| | • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | | |
| | | | | | | |
| 15 | Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table | 4 | | | <u> </u> | |
| 1 13 | | 7 | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | | |
| | • Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs | | | | | |
| | • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | | |
| | 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | | |
| | • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | | |
| 1 | | | | | | |
| 16 | Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 | 0 | | 1 | | |
| 1 | Furnish and set in place per plans, elevations and manufacturer's specifications | - | | | | |
| | p. armon and see in place per plans, elevations and manufacturer's specifications | L | L | | 1 | |

| 17 | Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal | 2 | | | |
|----|--|----|------|--|---|
| | Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip | | | | |
| | with hardware, stainless steel | | | | |
| | Faucet, splash type, rigid gooseneck, with standard handles | | | | |
| | | | | | |
| | Foot Pedal Valve | | | | |
| | Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts | | | | |
| | • P Trap | | | | |
| 18 | Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications | 4 | | | |
| 19 | Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per pla | 10 | | | |
| 20 | Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate | 6 | | | |
| | Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full- | | | | |
| | height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF, | | | | |
| | | | | | |
| | Refer to MEP for connections | | | | |
| | • 1 yr service/labor, 3 yr parts & warranty, standard | | | | |
| | Thermometer side: Door hinging to be determined | | | | |
| | Rear: Door hinging to be determined | | | | |
| | • 208V, 1P, 60hz | | | | |
| | Provide New Age 4338 Roll-in Rack at each unit. | | | | |
| 21 | Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate | 4 | | | |
| | Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full- | - | | | |
| | height doors, INTELA-TRAUL™ microprocessor controls. | | | | |
| | | | | | |
| | Refer to MEP for connections | | | | |
| | • 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard | | | | |
| | Thermometer side: Door hinging to be determined | | | | |
| | Rear: Door hinging to be determined | | | | |
| | • 120V , 1P, 60hz | | | | |
| | Provide New Age 4338 Roll-in Rack at each unit. | | | | |
| 22 | Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate | 0 | | | |
| | CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with | | | | |
| | integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz | | | | |
| | | | | | |
| | CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable | | | | |
| | Deluxe sneeze guard with glass overshelf and lights. 120V/1P/60hz | | | | |
| | CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide | | | | |
| | unit with grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated | | | | |
| | decor panels with cord/plug. | | | | |
| | | | | | |
| 27 | Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP | 0 | | | |
| | 16" shaft, Heavy Duty; Variable speed | | | | |
| | Power- 120V; 60 Hz; 6.2 Amps | | | | |
| | This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. | | | | |
| 28 | Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender | 1 | | | |
| 20 | | 1 | | | |
| | Ultra-heavy-duty, 3.75 HP commercial motor | | | | |
| | 3-speed selection and MAX PULSE to chop and mix | | | | |
| | Durable, full die-cast motor housing with rugged | | | | |
| | rubber feet to reduce vibration | | | | |
| | Power- 120V; 60Hz; 15 Amps | | | | |
| 29 | Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS | 1 | | | |
| | Furnish and place per plans | | | | |
| | Commercial microwave 10 touch pad control panel shall be | | | | |
| | programmable with the ability to program up to 100 menu | | | | |
| 1 | | | | | |
| | items with two multiple portions. Touch pad shall include | | | |] |
| 1 | Braille for ADA compliance. Cooking timer shall be 60 minute, | | | | |
| 1 | countdown style with a time entry option and an adjustable | | | | |
| | end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall | | | | |
| | be 1000 watts distributed by one magnetron with a rotating | | | | |
| | top antenna to provide superior even heating throughout the | | | | |
| | cavity. Durable door shall have a tempered glass window and | | | | |
| | a grab and go handle with a 900 | | | | |
| | + opening for easy access. An | | | | |
| 1 | 1 9 7 | | | | |
| 1 | interior light shall facilitate monitoring without opening the | | | | |
| 1 | door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate | | | | |
| | a 14" (356 mm) platter. | | | | |
| | Power: 120V; 60Hz; 15 Amp | | | | |
| | Install on a hanging shelf on an open space on the wall. | | | | |
| | | | | | |

| 28 | Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with | 2 | | | |
|----|--|---|--|--|--|
| | Clear Door - 120V or preapproval alternate | | | | |
| 29 | Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right | 2 | | | |
| | Hinge Solid Door, 115v or preapproval alternate | | | | |

Mobile Refrigerator (2) and mobile warmer (2) - Both should have sheet pan racks

| | IDEA Monterrey Park - 222 | SW 39th St, San A | Antonio, TX 78237 | | | | |
|------|--|-----------------------|-------------------|-------|-------------------------------|------------|--------------|
| Item | Description | Requested Quantity | Brand | Price | Installation Cost Per Unit | Total Cost | Vendor Notes |
| 1 | Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans, elevations and manufacturer's specifications • Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer • Cover to be stainless steel and hinged with condensate ring • Power pan tilt, tilting console with provision for faucet • Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition • Each unit to be 480V, 3 phase, 60 Hz, 12kw • One Year parts and labor warranty • (2) Faucet bracket assembly • (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer • (2) Stamling Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) • (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit) | 2 | | | | | |
| 2 | Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per plans, elevations and manufacturer's specifications. • Provide Blodgett full size convection oven model Mark V (double) compartment. • Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans. • Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous operation. • Unit to be electrically heated with three tubular heaters. • Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload protection. • Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. • Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60 minute timer. • Equip units with all standard features available on these units. • Double-Deck • Provide all stainless steel 8" legs. • Provide vent connector. • Warranty; provide Five year limited oven door warranty. • One-year parts and labor warranty. | 2 | | | | | |
| 3 | 3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF (requires 2 faucets) 1 ea K-453 Control Bracket, 14" x 16" (each) 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain | 1 | | | | | |
| 4 | Pre-Rinse Fauce assembly with add on faucet | 1 | | | | | |
| 5 | Wall / Splash mount faucet | 1 | | | | | |
| 6 | Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 Furnish and set in place per plans, elevations and manufacturer's specifications. • Water Filtration System Cartridge for Premium Quality Water • 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing • 12 gallon capacity • NEMA L6-30P Locking Cap in lieu of NEMA 6-30P • 208V, 1 phase 60 Hz, 24.0A | 0 | | | | | |

| 7 | Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate. | 1 | | | | |
|----|---|---|--|---|---|--|
| | Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length. | | | | | |
| | • Sink to be 18" x 24" with 18" drainboards each side. | | | | | |
| | | | | | | |
| | Wash sink compartment to be 11-1/2" deep with 11"H backsplash | | | | | |
| | • Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, | | | | | |
| | wall bracket. | | | | | |
| | Add-On-Faucet with 12" swing spout | | | | | |
| 8 | Pre-Rinse Fauce assembly with add on faucet | 1 | | | | |
| 9 | Ice Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice | 1 | | | | |
| | Maker, cube-style, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes | | | | | |
| | | | | | | |
| | (not stackable). | | | | | |
| | Refer to MEP for connections | | | | | |
| | 3 year parts & labor warranty | | | | | |
| | • 5 year parts & labor warranty on evaporator | | | | | |
| | • 5- year parts & 3- year labor warranty on compressor | | | | | |
| | | | | | | |
| | • Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter | | | | | |
| | cartridge, (NOT stand-alone; should be used in conjunction with primary water filter assembly) | | | | | |
| | • Ice Bin, 48"W x 34"D, 50"H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice | | | | | |
| | maker, stainless steel exterior, NSF | | | | | |
| | 6" adjustable stainless steel legs, std. | | | | 1 | |
| 10 | Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart | 1 | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | 1 | | | 1 | |
| | | | | | 1 | |
| | • 30"x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf | | | | 1 | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | | |
| | • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | | |
| | Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | | |
| | | | | | | |
| 11 | Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E | 1 | | | | |
| 1 | Furnish and set in place per plans, elevations and manufacturer's specifications | _ | | | | |
| | • Power; 120v,60Hz, 7.6 A. | | | | | |
| | | | | | | |
| 12 | Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table | 1 | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | | |
| | • Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and | | | | | |
| | under shelf. | | | | | |
| | TA-366 Reinforced understructure for undershelves (maximum | | | | | |
| | recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | | |
| | • SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, | | | | | |
| | | | | | | |
| | stainless steel, with drawer slides | | | | | |
| | Provide with 1-1/2" backsplash | | | | | |
| 13 | Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack Furnish and | 1 | | | | |
| | set in place per plans, elevations and manufacturer's specifications | | | | | |
| | Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf. | | | | | |
| | Provide table with one (1) pot rack to be center-mounted to table | | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | | |
| | • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | | |
| | 9 9 " , | | | | | |
| | • Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | 1 | |
| | | | | | | |
| 14 | Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table | 1 | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | | |
| | Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and | | | | | |
| | under shelf. | | | | | |
| | Provide One (1) Edlund can opener and mount to table per drawing. | | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | | |
| | | | | | 1 | |
| | • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | 1 | |
| | • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | | |
| | | | | | | |
| 15 | Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table | 4 | | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | | |
| | Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs | | | | 1 | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | 1 | |
| | • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | 1 | |
| | | | | | | |
| | • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | 1 | |
| | | | | | | |
| 16 | Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 | 2 | | 1 | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | | |
| | | | | | | |

| 17 | Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal | 3 | | | | | |
|-----|--|-----|---|---|---|----|---|
| | Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip | | | | | | |
| | with hardware, stainless steel | | | | | | |
| | Faucet, splash type, rigid gooseneck, with standard handles | | | | | | |
| | | | | | | | |
| | • Foot Pedal Valve | | | | | | |
| | • Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts | | | | | | |
| | • P Trap | | | | | | |
| 18 | Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications | 3 | | | | | |
| 19 | Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per pla | 6 | | | | | |
| 20 | Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate | 2 | | | | | |
| | Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full- | | | | | | |
| | height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF, | | | | | | |
| | Refer to MEP for connections | | | | | | |
| | • 1 yr service/labor, 3 yr parts & warranty, standard | | | | | | |
| | | | | | | | |
| | Thermometer side: Door hinging to be determined | | | | | | |
| | Rear: Door hinging to be determined | | | | | | |
| | • 208V, 1P, 60hz | | | | | | |
| | Provide New Age 4338 Roll-in Rack at each unit. | | | | | | |
| 21 | Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate | 3 | | | | | |
| | Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full- | | | | | | |
| | height doors, INTELA-TRAUL™ microprocessor controls. | | | | | | |
| | Refer to MEP for connections | | | | | | |
| | • 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard | | | | | | |
| | Thermometer side: Door hinging to be determined | | | | | | |
| | Rear: Door hinging to be determined | | | | | | |
| | | | | | | | |
| | • 120V , 1P, 60hz | | | | | | |
| | Provide New Age 4338 Roll-in Rack at each unit. | | | | | | |
| 22 | Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate | 2 | | | | | |
| | CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with | | | | | | |
| | integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz | | | | | | |
| | CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable | | | | | | |
| | Deluxe sneeze guard with glass overshelf and lights. 120V/1P/60hz | | | | | | |
| | CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide | | | | | | |
| | unit with grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated | | | | | | |
| | decor panels with cord/plug. | | | | | | |
| | | | | | | | |
| 27 | Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP | 1 | | | | | |
| _ · | 16" shaft, Heavy Duty; Variable speed | _ | | | | | |
| | Power- 120V; 60 Hz; 6.2 Amps | | | | | | |
| | | | | | | | |
| 28 | This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. | - 1 | | | | | |
| 28 | Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender | 1 | | | | | |
| | Ultra-heavy-duty, 3.75 HP commercial motor | | | | | | |
| | 3-speed selection and MAX PULSE to chop and mix | | | | | | |
| | Durable, full die-cast motor housing with rugged | | | | | | |
| | rubber feet to reduce vibration | | | | | | |
| | Power- 120V; 60Hz; 15 Amps | | | | | | |
| 29 | Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS | 1 | | | | | |
| | Furnish and place per plans | | | | | | |
| | Commercial microwave 10 touch pad control panel shall be | | | | | | |
| | programmable with the ability to program up to 100 menu | | | | | | |
| | items with two multiple portions. Touch pad shall include | | | | | | |
| | Braille for ADA compliance. Cooking timer shall be 60 minute, | | | | | | |
| | countdown style with a time entry option and an adjustable | | | | | | |
| | | | | | | | |
| | end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall | | | | | | |
| | be 1000 watts distributed by one magnetron with a rotating | | | | | | |
| 1 | top antenna to provide superior even heating throughout the | | | | | | |
| 1 | cavity. Durable door shall have a tempered glass window and | | | | | | |
| | a grab and go handle with a 90o | | | | | | |
| | + opening for easy access. An | | | | | | |
| | interior light shall facilitate monitoring without opening the | | | | | | |
| | door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate | | | | | | |
| | a 14" (356 mm) platter. | | | | | | |
| 1 | Power: 120V; 60Hz; 15 Amp | | | | | | |
| 1 | Install on a hanging shelf on an open space on the wall. | | | | | | |
| | motes on a nanging orien on an open space on the wan. | | 1 | ļ | 1 | I. | 1 |

| Γ | 28 | Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with | 1 | | | |
|---|----|--|---|--|--|--|
| | | Clear Door - 120V or preapproval alternate | | | | |
| Γ | 29 | Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right | 1 | | | |
| | | Hinge Solid Door, 115v or preapproval alternate | | | | |

Mobile Refrigerator and mobile warmer - Both should have sheet pan racks

| | IDEA Walzem - 6445 Walzem Rd, San Antonio, TX 78239 | | | | | | |
|------------------|--|-----------------------|-------|-------|-------------------------------|------------|--------------|
| Item | Description | Requested Quantity | Brand | Price | Installation Cost Per Unit | Total Cost | Vendor Notes |
| 1 | Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans, elevations and manufacturer's specifications • Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer • Cover to be stainless steel and hinged with condensate ring • Power pan tilt, tilting console with provision for faucet • Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition • Each unit to be 480V, 3 phase, 60 Hz, 12kw • One Year parts and labor warranty • (2) Faucet bracket assembly • (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer • (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) • (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit) | 2 | | | | | |
| 2 | Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per plans, elevations and manufacturer's specifications. • Provide Blodgett full size convection oven model Mark V (double) compartment. • Provide Blotgett full size convection oven model Mark V (double) compartment. • Provide Blotgett full size convection oven model Mark V (double) compartment. • Doors shall be stainless steel compartments, that accept five 18" x 26" standard full size bake pans. • Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous operation. • Unit to be electrically heated with three tubular heaters. • Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload protection. • Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. • Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200-500 degrees) with 60 minute timer. • Equip units with all standard features available on these units. • Double-Deck • Provide all stainless steel 8" legs. • Provide vent connector. • Warranty; provide Five year limited oven door warranty. • One-year parts and labor warranty. | 3 | | | | | |
| 3 4 5 6 | 3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF (requires 2 faucets) 1 ea K-453 Control Bracket, 14" x 16" (each) 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain Pre-Rinse Faucet assembly with add on faucet Wall / Splash mount faucet Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 Furnish and set in place per plans, elevations and manufacturer's specifications. • Water Filtration System Cartridge for Premium Quality Water • 3" (914 mm) Rubber Drain Hose with 10" (3048 mm) 1/4" Inlet Tubing | 1 1 1 0 | | | | | |
| | 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing 12 gallon capacity NEMA 16-30P Locking Cap in lieu of NEMA 6-30P 208V, 1 phase 60 Hz, 24.0A | | | | | | |

| 7 | Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate. | 1 | | | |
|-------------|---|---|--------------|----------|---|
| | Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length. | | | | |
| | • Sink to be 18" x 24" with 18" drainboards each side. | | | | |
| | | | | | |
| | Wash sink compartment to be 11-1/2" deep with 11"H backsplash | | | | |
| | • Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, | | | | |
| | wall bracket. | | | | |
| | Add-On-Faucet with 12" swing spout | | | | |
| 8 | Pre-Rinse Fauce assembly with add on faucet | 1 | | | |
| 9 | Ice Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice | 1 | | | |
| 9 | | 1 | | | |
| | Maker, cube-style, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes | | | | |
| | (not stackable). | | | | |
| | Refer to MEP for connections | | | | |
| | 3 year parts & labor warranty | | | | |
| | • 5 year parts & labor warranty on evaporator | | | | |
| | • 5- year parts & 3- year labor warranty on compressor | | | | |
| | | | | | |
| | Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter | | | | |
| | cartridge, (NOT stand-alone; should be used in conjunction with primary water filter assembly) | | | | |
| | • Ice Bin, 48"W x 34"D, 50"H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice | | | | |
| | maker, stainless steel exterior, NSF | | | | |
| | 6" adjustable stainless steel legs, std. | | | | |
| 10 | Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart | 1 | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | _ | | | |
| | | | | | |
| | • 30" x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| | 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | |
| | Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | |
| | | | | | |
| 11 | Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E | 1 | | | |
| 1 | Furnish and set in place per plans, elevations and manufacturer's specifications | - | | | |
| | • Power; 120v,60Hz, 7.6 A. | | | | |
| - 40 | | | | | |
| 12 | Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table | 1 | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | |
| | • Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and | | | | |
| | under shelf. | | | | |
| | TA-366 Reinforced understructure for undershelves (maximum | | | | |
| | recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| | • SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, | | | | |
| | | | | | |
| | stainless steel, with drawer slides | | | | |
| | Provide with 1-1/2" backsplash | | | | |
| 13 | Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack Furnish and | 1 | | | |
| | set in place per plans, elevations and manufacturer's specifications | | | | |
| | • Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf. | | | | |
| | Provide table with one (1) pot rack to be center-mounted to table | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| | 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | |
| | 9 9 | | | | |
| | Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | |
| | | | | | |
| 14 | Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table | 1 | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | |
| 1 | Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and | | | | |
| 1 | under shelf. | | | | |
| | Provide One (1) Edlund can opener and mount to table per drawing. | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| | • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | |
| | • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | |
| 1 | - 2 Deluke Drawers, 10 W X 20 D X 3 Greep Grawer pair insert, stainless Steel, with grawer sliges | | | | |
| | | | | - | |
| 15 | Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table | 4 | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | |
| | Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs | | | | |
| | Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) | | | | |
| | 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) | | | | |
| 1 | • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides | | | | |
| | 2 Science Statistics, 25 to A 25 deep drawer pair insertigationics seed, with drawer states | | | | |
| 16 | Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 | 1 | + | <u> </u> | + |
| 10 | | 1 | | | |
| | Furnish and set in place per plans, elevations and manufacturer's specifications | | | | |

| 17 | Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal | 4 | | | | | |
|----|--|-----|---|---|-----|---|--|
| | Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip | | | | | | |
| | with hardware, stainless steel | | | | | | |
| | • Faucet, splash type, rigid gooseneck, with standard handles | | | | | | |
| | | | | | | | |
| | Foot Pedal Valve | | | | | | |
| | Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts | | | | | | |
| | • P Trap | | | | | | |
| 18 | Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications | 4 | | | | | |
| 19 | Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per pla | 10 | | | | | |
| 20 | Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate | 6 | | | | | |
| | Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full- | | | | | | |
| | height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF, | | | | | | |
| | Refer to MEP for connections | | | | | | |
| | • 1 yr service/labor, 3 yr parts & warranty, standard | | | | | | |
| | | | | | | | |
| | Thermometer side: Door hinging to be determined | | | | | | |
| | Rear: Door hinging to be determined | | | | | | |
| | • 208V, 1P, 60hz | | | | | | |
| | Provide New Age 4338 Roll-in Rack at each unit. | | | | | | |
| 21 | Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate | 4 | | | | | |
| | Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full- | | | | | | |
| | height doors, INTELA-TRAUL™ microprocessor controls. | | | | | | |
| | Refer to MEP for connections | | | | | | |
| | • 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard | | | | | | |
| | Thermometer side: Door hinging to be determined | | | | | | |
| | Rear: Door hinging to be determined | | | | | | |
| | | | | | | | |
| | • 120V , 1P, 60hz | | | | | | |
| | Provide New Age 4338 Roll-in Rack at each unit. | | | | | | |
| 22 | Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate | 2 | | | | | |
| | CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with | | | | | | |
| | integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz | | | | | | |
| | CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable | | | | | | |
| | Deluxe sneeze guard with glass overshelf and lights. 120V/1P/60hz | | | | | | |
| | CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide | | | | | | |
| | unit with grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated | | | | | | |
| | decor panels with cord/plug. | | | | | | |
| | | | | | | | |
| 27 | Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP | 1 | | | | | |
| | 16" shaft, Heavy Duty; Variable speed | _ | | | | | |
| | Power- 120V; 60 Hz; 6.2 Amps | | | | | | |
| | | | | | | | |
| 28 | This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. | - 1 | | | | | |
| 28 | Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender | 1 | | | | | |
| | Ultra-heavy-duty, 3.75 HP commercial motor | | | | | | |
| | 3-speed selection and MAX PULSE to chop and mix | | | | | | |
| | Durable, full die-cast motor housing with rugged | | | | | | |
| | rubber feet to reduce vibration | | | | | | |
| | Power- 120V; 60Hz; 15 Amps | | | | | | |
| 29 | Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS | 1 | | | | | |
| 1 | Furnish and place per plans | | | | | | |
| 1 | Commercial microwave 10 touch pad control panel shall be | | | | | | |
| 1 | programmable with the ability to program up to 100 menu | | | | | | |
| | items with two multiple portions. Touch pad shall include | | | | | | |
| 1 | Braille for ADA compliance. Cooking timer shall be 60 minute, | | | | | | |
| 1 | countdown style with a time entry option and an adjustable | | | | | | |
| 1 | | | | | | | |
| | end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall | | | | | | |
| 1 | be 1000 watts distributed by one magnetron with a rotating | | | | | | |
| | top antenna to provide superior even heating throughout the | | | | | | |
| | cavity. Durable door shall have a tempered glass window and | | | | | | |
| | a grab and go handle with a 90o | | | | | | |
| 1 | + opening for easy access. An | | | | | | |
| 1 | interior light shall facilitate monitoring without opening the | | | | | | |
| | door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate | | | | | | |
| | a 14" (356 mm) platter. | | | | | | |
| | Power: 120V; 60Hz; 15 Amp | | | | | | |
| | Install on a hanging shelf on an open space on the wall. | | | | | | |
| | mistan on a manging site in on an open space on the want. | | 1 | L | l . | 1 | |

| Γ | 28 | Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with | 1 | | | |
|---|----|--|---|--|--|--|
| | | Clear Door - 120V or preapproval alternate | | | | |
| ſ | 29 | Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right | 1 | | | |
| | | Hinge Solid Door, 115v or preapproval alternate | | | | |

Mobile Refrigerator and mobile warmer - Both should have sheet pan racks

| | Buy Out Optional | | |
|-----------|--|--------------|---------------------|
| Estimated | | Unit Buy Out | |
| Qty. | Description | Price | Total Buy Out Price |
| 8 | Tilting skillet | | |
| 11 | Convection Oven | | |
| 4 | 3 Compartment Sink | | |
| 4 | Pre-Rinse Faucet assembly with add on faucet | | |
| 4 | Wall / Splash mount faucet | | |
| 1 | Hot Water Dispenser | | |
| 4 | Two Compartment Sink | | |
| 4 | Pre-Rinse Faucet assembly with add on faucet | | |
| 4 | Ice Maker and Bin | | |
| 4 | Work Table/ Cart | | |
| 4 | Food Processor | | |
| 4 | Work Table | | |
| 4 | Work Table w/ Pot Rack | | |
| 4 | Work Table w/ drawers and can opener | | |
| 16 | Work Table w/ drawers | | |
| 4 | Mobile Pan Rack | | |
| 12 | Hand Sink | | |
| 15 | Utility Cart | | |
| 36 | Refrigerator Rack, Roll-in | | |
| 20 | Roll-Thru Heated Cabinet | | |
| 15 | Roll-Thru Refrigerator Cabinet | | |
| 6 | Serving Counter | | |
| 3 | Immersion Blender | | |
| 4 | Commercial Food Blender | | |
| 4 | Commercial Microwave | | |
| 6 | Mobile Heated Holding | | |
| 6 | Mobile Cooling Holding | | |