EQUIPMENT PRICING TEMPLATE RFP #17-CNPKFL-0424

Vendor All Specification are provided on manufacturer description. The awarded vendor is responsible to ensure that equipment meets the space Information needs of the identified campus.

	IDEA Donna - 401 S 1st	St, Donna, TX 7853					
em	Description	Requested Quantity	Brand	Price	Installation Cost Per Unit	Total Cost	Vendor Notes
1	Tilting Skillet - Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans, elevations and manufacturer's specifications • Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer • Cover to be stainless steel and hinged with condensate ring • Power pan tilt, tilting console with provision for faucet • Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition • Each unit to be 480V, 3 phase, 60 Hz, 12kw • One Year parts and labor warranty • (2) Faucet bracket assembly • (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer • (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) • (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)	3					
2	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per plans, elevations and manufacturer's specifications. Provide Blodgett full size convection oven model Mark V (double) compartment. Provide Blodgett full size convection oven model Mark V (double) compartment. Doors shall be stainless steel compartments, that accept five 18" x 26" standard full size bake pans. Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous operation. Unit to be electrically heated with three tubular heaters. Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload protection. Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60 minute timer. Equip units with all standard features available on these units. Double-Deck Provide all stainless steel 8" legs. Provide vent connector. Warranty; provide Five year limited oven door warranty. One-year parts and labor warranty. Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total	4					
3	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF (requires 2 faucets) 1 ea K-453 Control Bracket, 14" x 16" (each) 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain	1					
4	Pre-Rinse Faucet assembly with add on faucet	1	·				
<u>5</u> 6	Wall / Splash mount faucet Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 Furnish and set in place per plans, elevations and manufacturer's specifications. • Water Filtration System Cartridge for Premium Quality Water • 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing • 12 gallon capacity • NEMA L6-30P Locking Cap in lieu of NEMA 6-30P • 208V, 1 phase 60 Hz, 24.0A	1					
7	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate. Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length. Sink to be 18" x 24" with 18" drainboards each side. Wash sink compartment to be 11-1/2" deep with 11"H backsplash Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket. Add-On-Faucet with 12" swing spout	1					

9	Ice Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice Maker, cube-style, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes (not stackable). • Refer to MEP for connections • 3 year parts & labor warranty • 5 year parts & labor warranty on evaporator • 5- year parts & 3- year labor warranty on compressor • Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter cartridge, (NOT stand-alone; should be used in conjunction with primary water filter assembly) • Ice Bin, 48°W x 34°D, 50°H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice maker, stainless steel exterior, NSF • 6" adjustable stainless steel legs, std.	1			
10	Work Table / Cart - Manufacturer/Model: Counter/Craft Lite Model Prep Table/Cart Furnish and set in place per plans, elevations and manufacturer's specifications • 30"x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	1			
11	Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E Furnish and set in place per plans, elevations and manufacturer's specifications • Power; 120v,60Hz, 7.6 A.	1			
12	Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and under shelf. • TA-366 Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides • Provide with 1-1/2" backsplash	1			
13	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf. • Provide table with one (1) pot rack to be center-mounted to table 36" x 96" • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	2			
14	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under shelf. • Provide One (1) Edlund can opener and mount to table per drawing. • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	1			
15	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	4			
16	Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 Furnish and set in place per plans, elevations and manufacturer's specifications	1			
17	Hand Sink - IMC/Teddy Model CSW-25 or pre-approved equal Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with hardware, stainless steel • Faucet, splash type, rigid gooseneck, with standard handles • Foot Pedal Valve • Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts • P Trap	3			
18	Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications	4			

19	Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per plans, elevations and manufacturer's specifications	10			
20	ROII-Thru Heated Cabinet - Traulsen Model AlH132LP-FHS or pre-approved alternate Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF, Refer to MEP for connections 1 yr service/labor, 3 yr parts & warranty, standard Thermometer side: Door hinging to be determined Rear: Door hinging to be determined 208V, 1P, 60hz Provide New Age 4338 Roll-in Rack at each unit.	6			
21	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-height doors, INTELA-TRAUL™ microprocessor controls. • Refer to MEP for connections • 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard • Thermometer side: Door hinging to be determined • Rear: Door hinging to be determined • Rear: Door hinging to be determined • 120V, 1P, 60hz • Provide New Age 4338 Roll-in Rack at each unit.	4			
22	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe sneeze guard with glass overshelf and lights. 120V/1P/60hz CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated decor panels with cord/plug.	2			
23	Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP 16" shaft, Heavy Duty; Variable speed Power- 120V; 60 Hz; 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet.	1			
24	Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power- 120V; 60Hz; 15 Amps	1			
25	Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp Install on a hanging shelf on an open space on the wall.	1			
26	Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with Clear Door - 120V or preapproval alternate	2			
27	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan	15			
28	Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right Hinge Solid Door, 115v or preapproval alternate	2			
29	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan	15			
		•	•	•	•

Mobile Refrigerator (2) and mobile warmer (2) - Both should have sheet pan racks

	IDEA Weslaco Pike - 1000 E Pik	ka Rhyd Wasiaca T	V 79506				
Item	Description	Requested	A 70330	T T	Installation	1	
	Description		Brand	Price		Total Cost	Vendor Notes
		Quantity			Cost Per Unit		
1	Tilting Skillet- Tilting Skillet- Tilting Skillet BRAISING PAN, ELECTRIC (2 REQ'D) Vulcan Model VE40 Dimensions: 40.5(h) x 46(w) x 35.5(d) Braising Pan, electric, 40-gallon capacity, 16 kW FastBatch™ embedded heating technology, 46" wide open base, manual tilt, 9" deep stainless steel pan with gallon markings, pouring lip & removable strainer, spring assist cover with drip edge, pan holder, water tight solid state controls, includes L faucet bracket, 12" stainless steel legs with adjustable flanged feet, cULus, UL EPH Classified 2 ea - 1 year limited parts & labor warranty, standard 2 ea - K-12 School Nutrition extended warranty extends the warranty for 12 months beyond the 12 month Original Equipment Warranty, not to exceed 24 months from date of installation 2 ea - 480V/60/3-ph, 16 kW, 20.0 amps, direct wire 2 ea - Model SGLTS 12NZL SINGLE Pantry Deck-Mount Faucet, 12" swivel spout, includes 4" & 12" riser, NSF & Lead Reduction Compliant (Note: water connection required)	2					
2	Convection Oven - CONVECTION OVEN, ELECTRIC (2 REQ'D) Vulcan Model VC44ED Dimensions: 70(h) x 40(w) x 42.25(d) Convection Oven, electric, double-deck, standard depth, solid state controls, temperature range 150* to 500°F, 60 minute timer with audible alarm per oven, oven cool switch for rapid cool down, independently operated stainless steel doors with double pane windows, porcelain enamel on steel oven interiors, (5) nickel plated racks per oven, stainless steel front, top, sides & 8"H legs, (2) 1/2 HP two speed oven blower-motors, 12 kW each section, NSF, cUL, UL, ENERGY STAR* 2 ea - 1 year limited parts & labor warranty, standard 2 ea - K-12 School Nutrition extended warranty extends the warranty for 12 months beyond the 12 month Original Equipment Warranty, not to exceed 24 months from date of installation 4 ea - (2) 480v/60/3-ph, 30 amps total, priced per oven 4 ea - Simultaneous doors, both ovens 2 ea - SST legs, standard	2					
3	3 Compartment Sink -						
	Three-Compartment Sink - Manufacturer/Model: Eagle Group Model FN2060-3-18-14/3-TB, or pre- approved alternate. Eagle Spec-Master* Three-Compartment Sinks. Unit constructed of 14-gauge 300 series, 18-8 stainless steel throughout. Sink bowls coved with a full ¾ radius and shall have a 14" high water level and requires 2 faucets. Overall dimensions 27" deep, 102" long. Left & right-hand 18" drainboards 7" creased for positive drainage. 9¾ high backsplash with 1" upturn and tile edge. Legs to be 1¾" O.D., stainless steel, with stainless steel gussets, stainless steel crossbracing and adjustable stainless steel bullet feet. 18" undershelves left and right under drainboards. Mount Cantilever Shelf Through Splash left and right with 24" overshelf Three (3) each TB Support Bracket, for lever waste drain handle. Three (3) each 341189 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections	1					
4	B-0133-16-B08EL T&S Pre-Rinse, Spring Action, 8" Wall Mount, 16" Add-On, Wall Bracket, B-0108 Spray Valve.	1					
5	B-0230-02 8" T&S Wall Mount Base Faucet, 18" Swing Nozzle, 2.2 GPM Aerator, Lever Handles	1		1			
6	Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 Furnish and set in place per plans, elevations and manufacturer's specifications. • Water Filtration System Cartridge for Premium Quality Water • 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing • 12 gallon capacity • NEMA 16-30P Locking Cap in lieu of NEMA 6-30P • 208V, 1 phase 60 Hz, 24.0A	0					
7	Two Compartment Sink - Two-Compartment Sink - Manufacturer/Model: Eagle Group Model FN2032-2-18-14/3-TB, or pre- approved alternate. Eagle Spec-Master® Two-Compartment Sinks. Unit constructed of 14-gauge 300 series, 18-8 stainless steel throughout. Sink bowls coved with a full %" radius and shall have a 14" high water level and requires 2 faucets. Bowls are 16" wide, 20" front-to-back, 14" deep compartments. Overall dimensions 27"deep, 72" long. • Left & right-hand drainboards 18" Drainboards shall be "V" creased for positive drainage. 9%" high backsplash with 1" upturn and tile edge. Legs to be 1%" O.D., stainless steel, with stainless steel gussets, stainless steel crossbracing and adjustable stainless steel bullet feet. • 18" undershelves left and right under drainboards. • Two (2) each TB Support Bracket, for lever waste drain handle. • Two (2) each 341189 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections. • One (1) each B-0133-16-B08EL Pre-Rinse, Spring Action, 8" Wall Mount, 16" Add-On, Wall Bracket, B-0108 Spray Valve. • One (1) each B-0230-02 8" Wall Mount Base Faucet, 18" Swing Nozzle, 2.2 GPM Aerator, Lever Handles	1					

8	Pre-Rinse Faucet assembly with add on faucet	1			
9	Tre-Mine Later assembly with add on laddet				
	The Manitowoc Ice IYT-0420A-161/D-420 Indigo NXT [™] ice maker with bin can provide a 460-pound maximum daily output. Ice thickness is measured by an acoustical sensing probe, ensuring each cycle is uniform. Through the control system, preventive maintenance provides users with diagnostic feedback. If there is an issue in the foodzone, the operator can easily access the area through the swing-out front door. This access design also simplifies cleanup, and some of the parts are removable and made with AlphaSan® antimicrobial. Weight 136 Width 22 Depth 25 Height 22 Voltage and faces	1			
10	Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart				
10	Furnish and set in place per plans, elevations and manufacturer's specifications 30"x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	1			
11	Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E				
	Furnish and set in place per plans, elevations and manufacturer's specifications	1			
	• Power; 120v,60Hz, 7.6 A.				
12	Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and under shelf. • TA-366 Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides • Provide with 1-1/2" backsplash	1			
13	Worktable Manufacturer Eagle Group Spec-Master® Series Worktable, 72"W x 30"D, 14/300 series stainless steel top, rolled edge on front & back, adjustable 18/300 series stainless steel undershelf with marine edge, Uni-Lok® gusset system, (4) stainless steel legs & adjustable bullet feet, NSF • Model TM72PR Pot Rack, table mount, 64"W x 20"D, triple-bar design with tubular table supports, constructed of 3/16" x 2" stainless steel flat bar, includes (18) double-pronged pot hooks, for 72"W table, NSF	1			
14	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under shelf. • Provide One (1) Edlund can opener and mount to table per drawing. • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	1			
15	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	4			
16	Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 Furnish and set in place per plans, elevations and manufacturer's specifications	0			
17	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with hardware, stainless steel • Faucet, splash type, rigid gooseneck, with standard handles • Foot Pedal Valve	2			
18	Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts P Trap Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications				

12 International Control Contr						
United Series (All Distances (All Distances) (
elegistativité, entrouted information patient for 12 x 10 to 16 x 10 x 10 to 10 x 10 x 10 to 10 to 10 x 10 to 10 to 10 x 10 to		New Age Model 4338 Dimensions: 64(h) x 21.5(w) x 26(d)				
partners evid cateurs, Ps. Mode in U.A., justines face intolory less time and provide partners approved expented very described provides and provide		Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing (non-				
Softon and carrier, In Francis in Link, Statistical Recovers (actives gainet services and actives defects.) 20 Sa Linker Carrier - Tradeon food All (1921) Fifth or or engineered elements. Synchronic Lands, 1981 First Carrier Carrier, 1981 First Carrier approximation in the Carrier Carrier, 1981 First Carrier Carrier, 1981 First Carrier Carrier, 1981 First Carrie		adjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights, (4) 5"	10			
2 Nat The Marked Callest. Trade and Accresions. National part of controls of controls. 2 Nat The Marked Callest. Trade and Anti-National Processing Support of Streets. 2 Sec Use in control Callest. Trade and Anti-National Processing Support of Streets. 3 Processing Callest. Anti-National Processing Support of Streets. 4 Year Institution Callest. Trade and Support Streets. 4 Year Support Sup						
20. Bit Mark Marked Calles, T., Tarakins Model, 2015.73.97 As or pro-approach alternation, state of all religion disors, since translated Calles, distance, and controlling and controlling and the controllin						
Special control Colonian (Feb. Polity, spife controllers), spife controllers of injurishing files (Polity Polity P		10 ea - Lifetinie guarantee against rust & con osion. Lifetinie guarantee against worksmanship and material defects.				
Size Clark Refact Californi, Cell Plant, Jedinordinand, danies and category and public plants. **Public Plants of Comments of State Plants of Sta	20	Roll-Thru Heated Cabinet - Traulsen Model AIH132I P.FHS or pre-approved alternate				
METRA TRAUM* microgramsors controls, 5° algorizable sk-leg, 1867, **Selection (MPC) or connections **Personnecte size: User largering to be determined **Personnecte size: User largering to size size size size size size size size						
* Feder to MPF for connections ** I year work (white) is a year in the security of the determined ** Horizonean size (both Inline) to the determined ** Horizonean size (both Inline) ** Horizonean size (both Inl						
* Ye service/book.n. 24 parts & servancy, manador * *Themserves (See Door Imaging to be determined * **Cerc Door Pringing to be determined * **Provide (New page 138) Roll his high at clear unit. 2. RACH-HD DIPLAY REPORDINATION, 1 SECTION Tratians Novel, Novel 12 parts (Print Report Novel) (1997) Report (1997						
**Thermoniters state Dear halping to be determined **Herr Door Uniting to the decrease state and the state of						
Pear Door Integrate to be determined		• 1 yr service/labor, 3 yr parts & warranty, standard	6			
- 2009; 19; 5011c Provide Way Age 1338 (Tollin Risk at earth unit Provide Way Age 1338 (Tollin Risk at earth unit Provide Way Age 1338 (Tollin Risk at earth unit Provide Way Age 1348 (Tollin Risk) (T		Thermometer side: Door hinging to be determined				
- 2009; J.P. 2008 - Product Now Jay - 13.5 Rigidin Black at each unit. 2 IN IRACH-RY ORDEA'S REPORTEDIATION, 1.5CCTOM - Special Market Production of Section (1997) and the production of the		Rear: Door hinging to be determined				
**Provide have Age 43.58 (bolin files at a rate to mit. 18		• 208V, 1P, 60hz				
12 MACHEN DISPLAY REFERENCE AS 157(0) In SECURITY CONTINUES AND STATES AS 157(0) \$27,88(0) ± 35(0) \$5(0) \$5(0)\$ Special in Reference As 157(0) Proceedings of the Continues of Display, one-exciton, 24,20 at 1, set for Continues of Display, and Associated Display, and						
Travlaten Mode Art 123/WIT-Fire Dimensions 83.29(1) 4 29.88(n) x 356(0) Spect-Line Refligitation, Reserving Logisty, on-section x 20 m., self-contained refligeration, Sury Clear*** contained the Refligitation Reserving Logisty, on-section x 20 m., self-contained refligeration, Sury Clear*** contained and the Refligitation Reserving Logisty, which will be a self-contained the Reserving Logisty Lo						
Spec-Lime Refrigeration, Reactive To Diplay, one-section, 24.2 cm. B., self-contained refrigeration, Sary/Clear [®] Condenses, standless steel station, duminum memoria, standard order, which file helping based one doors with \$2.0 cm. Sary/Clear [®] Condenses, standless steel station, and standard refrigeration, for "diplatable basiness steel legs, 11" bit you. (No. 1) 4 cm. 11.94/100 cm. 8 cm. standard refrigeration, standard 4 cm. Download Standard Standard 5 cm. on bit was a standard definition of the standard standard 5 cm. on bit was a standard definition of the standard control of the standard cont		·				
abuminum interior, standard depth, wide full-height glass door or doors with EC-Clean Galases, interior lights, [3] adjustable we're shelves per section, microprocessor controls, or "adjustable standard seed or "adjustable see						
section, microprocessor controls, 6" adjustable stanless steel legs, 17, 51 PF, CHUN, NSF 4 ex - 12-17/90(2) -45, 16, 30 anps, will cord 8 A ERMA -15-5; standard 4 ex - 12-17/90(2) -45, 16, 30 anps, will cord 8 A ERMA -15-5; standard 5 2 ex - Universal tray sides for 11, 13* 24° or 70 (12 ** 14* 16* or 71) 24 ** 24° pans -9er pair 1 2 ex - Creater, 6" Pilly fort of -1 2 2 Serving Counter - Countercards Model SERVING COUNTER or pre-approved alternate CounterCraft Modelin Froit Food Unit, Clasmitt, Two (2), with Netro GRSSP -55 Sult-to Installed Serving Counter or Countercards Model SERVING COUNTER or pre-approved alternate CounterCraft Modelin Froit Food Unit, Clasmitt, Two (2), with Netro GRSSP -55 Sult-to Installed Serving Counter Countercards Model SERVING COUNTER or pre-approved alternate CounterCraft Modelin Froit Food Unit, Clasmitt, Two (2), with Netro GRSSP -55 Sult-to Installed Serving Counter Counter Counter Grssp -10 (14 ** 12 *						
4 es - 5-year parts it, labor and 7-year compressor, standard Visit www.trasher.com for details 4 es - 15-undrad refrigerant, tunded 4 es - 5-undrad refrigerant, tunded 3 es - 5-undrad refrigerant, tunded 3 es - 5-undrad refrigerant, tunded 4 es - 5-undrad refrigerant, tunded 5 es - 5-undrad refrigerant, tunded 5 es - 5-undrad refrigerant, tunded 5 es - 5-undrad refrigerant, tunded 6 es - 5-undrad refrigerant, tunded refrigerant refri						
4 e.e. 150-(60)2-19, 8.6 amps, with cord & REMA-S19, standard 4 e.e. Standard refrigerant strandard 4 e.e. Door hinged on right, standard 3 2e.e. "Unless lit by sides for [13] 32c" or (2) 12" 12" 20" pans-per pair 4 f. Catters, 6" high let of 14 4 f. Catters, 7" high let of 14 4 f. Cat		section, microprocessor controls, 6" adjustable stainless steel legs, 1/3 HP, cULus, NSF				
4 e.e. 150-(60)2-19, 8.6 amps, with cord & REMA-S19, standard 4 e.e. Standard refrigerant strandard 4 e.e. Door hinged on right, standard 3 2e.e. "Unless lit by sides for [13] 32c" or (2) 12" 12" 20" pans-per pair 4 f. Catters, 6" high let of 14 4 f. Catters, 7" high let of 14 4 f. Cat		4 ea - 6-year parts & labor and 7 year compressor, standard. Visit www.traulsen.com for details				1
4 ea - Sort-highed on right, standard 4 ea - Boort hinged on right, standard 52 ea - Universal fave yaldeds for (\$11.87 x20" or (\$21.47 x20" pars- per pair 12 ea - Creates, O" Right lett of 4 12 ea - Creates, O" Right lett of 4 13 - Cautes, O" Right lett of 4 14 - Cautes, O" Right lett of 4 15 - Cautes, O" Right lett of 4 15 - Cautes, O' Right lett of 4 16 - Cautes (Cautes Cautes Counter Cautes Counter Cautes And Augustable Debus energe guard with plass overhelf and lights, 1200/17/F/ORIs (200/17/F/ORIs 200/17/F/ORIs 200/17/F/OR			4			1
4 ea - Door hinged on right, standard 22 ea - Universal tary side for (1) silf*26** or (2) 14**18** or (2) 12** x2° pans-per pair 22 ea - Credit for standard coated shelf, debuct 4.1** Castras, or high test of (1) 4.1** Castras, or high test of (1) 22 Serving Counter - Countercart Model strong Counter - Countercart Models strong Counter - Countercart - Countercart Models strong Counter - Countercart - C						
Size or Universal tray sides for (1) 18 **25" or (2) 18**x8" or (2) 12* x 20" pans- per pair 12 ea - Credit for standard casted shelf, deduct 4 at - Casters, 6" high (set of 4) 22 Sewing Counter-Counteract Model SERVING COUNTER or pre-approved alternate CounterCraft Models FREVING COUNTER or pre-approved alternate CounterCraft Models FREVING COUNTER or pre-approved alternate CounterCraft Models from Day, with Adjustable Deluse sensee guard and highs. 2009/17/6/mb. 2200/17/6/mb. CounterCraft Models Recessed Frost Unit, Quantity: Two (1), with F18 2. Provide counter with cord and play, with Adjustable Deluse useree guard with glass cerebral draights. 2009/17/6/mb. CounterCraft Postoria (1) and play. 2009/17/6/mb. 2						1
12 ea - Credit for Standard coated shelf, deduct 4 at - Castes, 6 - Tight for Counter Cath Model a Fort Count of Cath All 22 Serving Counter - Countercraft Model a Fort Count Unit, Quantify, Two (2), with Flatco CRSBR -85 Sult in Heated Shelf, Provide counter with integral stainless steed cutting surface, cord and policy, with Adjustable Delaws energe guard and lights, 2009/19/60hz 2009/19/60hz 2009/19/60hz CounterCraft Modelar Records Forts Link, Quantify Two (2), with Flatco Counter with ord and policy, with Adjustable Delaws energe guard with glass overshelf and lights, 1200/19/60hz CounterCraft A Peleonic Challer Two (1), SCM 1-88 Molly) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with grommeted ut outs for PDS cord access, each drawer with oil. Cashler unit to be mobile. Provide unit with laminated decor panels with coordinate of the Counter of t						1
4 st - Castern, 6" high, let of 4) 22 Service Gouther - Counterd Model SERVING COUNTER or pre-approved alternate CounterCraft Modified in the Food Unit, Quantity: Two (2), with Hatco 6858 - 365 8 bill in Heated Seleft Provide counter with integral stainless steel exiting surface, cod and play, with Adjustable Delives needer goal and lights. 2009/19/6/bil. CounterCraft Modified Recessed Frost Unit, Quantity: Two (2), with F18-2. Provide counter with cord and play, 2009/19/6/bil. CounterCraft 2-Persons Casher Unit (SES-148-MOD) with stainless steed tray sides of both sides of unit on fixed brackets: Provide unit with adjustable Delives needer guard with glass overheld and lights. 2009/19/6/bil. CounterCraft 2-Persons Casher Unit (SES-148-MOD) with stainless steed tray sides of both sides of unit on fixed brackets: Provide unit with unimated due on the five Coord access, each drawer with Unit. Casher unit to be mobile. Provide unit with luminated due on the five Coord access, each drawer with Unit. Casher unit to be mobile. Provide unit with luminated due on the five Coord access, each drawer with Unit. Casher unit to be mobile. Provide unit with luminated due on the five Coord access, each drawer with Unit Casher unit to be mobile. Provide unit with luminated due on the five Coord access and the five Coord access and the coord access and the coord access and the five Coord access and the coord access and the coord access and the coord access and the five Coord access and the c						
Serving Counter Countercraft Module For Odo Unit, Cuantry, 100 (2), with Hastor Soft-95-95 bill-1 releated Shelf. Provide counter with integral staniess steel cutting surface, cord and play, with Aglistable Deliuse sneeze guard and lights. 2089/19/60h; 2009/19/60h;						
CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSB-F-5-5 Sull-tin leated Shelf Provide counter with integral stainless steel cutting surface, cord and play, with Adjustable Peluse sense gard and lights. 2007/HORD: CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with F18 2. Provide counter with cord and play, with Adjustable Deluse sneeze guard with glass oversheld and lights. 1200/HORD: CounterCraft 2-Person Cashier Unit (SCSI-45-MOD) with stainless steel tray sides of both sides of unit on fixed brackets. Provide unit with grommeted cut outs for POS cord access, cash drawer with tilli. Cashier unit to be mobile. Provide unit with Laminated decor panels with cord/plug. 28 Immersion Blender - Manufacturer/Model: Warning WSB60 Big Silk 16* Variable Speed Immersion Blender - 1 HP 15* Harf, Heavy Duty, Yazhable Speed Power: 1209; 65 Bir, 6.2 Amps This registers a drop-down outed over a central work table and a wall outlet over the tilt skillet. 24 Commercial Mod Blender - Manufacturer/Model: Warning Model No. CB15P - 1 Callion Heavy Duty Blender Ultra-heavy-duty, 3.75 Hor Commercial micro outlet over the Unit skillet. 3-speed selection and MAX PULSS to chop and mix Durable, full dic-cast moth housing with rugged rubber feet to reduce vibration Power-1209; 68 Bir, 15 Amps Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plant by to program up to 100 menu items with two multiple portions. Touch pad shall be programmable with the sality to program up to 100 menu items with two multiple portions. Touch pad shall include end of cycle waddle signal, the ordinary of the control panel shall be ordinary. Countdown Style with a sime entry option and an adjustable end of cycle waddle signal. He ordinary of the control panel shall be ordinary. Countdown Style with a sime entry option and an adjustable end of cycle waddle signal. He ordinary of the salid and the control panel shall be ordinary. In the part of the control panel shall be		4 st - Casters, 6" high (set of 4)				
CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hasto GRSP-3-6 Sulli-in Heated Shelf, Provide counter with integral stanless steel cutting surface, cord and plays, with Algustable Polluss enserge agrand with glass oversheld and glish. 120/17(670): CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and play, with Algustable Deluss enserge guard with glass oversheld and glish. 120/17(670): CounterCraft 2-Person Cashier Unit (CSC4-8-MOD) with stanless steel tray sildes of both sides of unit on fixed brackets. Provide unit with grommeded cut outs for POS cord access, cash drawer with Uli. Cashier unit to be mobile. Provide unit with aminated decor panels with cord/plug. Immersion Blender - Manufacturer/Model: Warring WS600 Big Silk 10* Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15* fhaff, Heavy Duty, Variable Speed Immersion Blender - 1 HP 15*	22	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate				
scel cutring surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 289/17/60hz CounterCrief Modular Reseased Frost Unit, Cutanitry. Two (2), which adjustable Deluxe sneeze guard with glass overshelf and lights. 1290/19/60hz CounterCrieft 2-Person Canism Unit (SCI-4-AMO) with stainless steel tray sides of both sides of unit on fixed brackets. Provide unit with grommeted cut outs for POS cord access, cash drawer with Itili. Cashier unit to be mobile. Provide unit with laminated decor panels with cord/plug. 23 Immersion Blender - Manufacturer/Model: Waring WS860 Big Stilk 16° Variable Speed Immersion Blender - 1 HP 16° shaft, heavy Duty, Variable speed Power 220%; 60 Hz, 62 Amps This requires a drop down outlet over a central work table and a wall outlet over the tilt skillet. 24 Commercial Food Brender - Manufacturer/Model: Waring Model No. C815P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAN PULS Et on boy and mix Durable, full dic-east motor housing with rugged rubber Feet to reduce bilation on the Visitation Power - 120%; 60 Hz, 55 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place pee plans. Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave output shall be programmable with the ability to program up to 100 menu teems with how multiple protrinas. Touch padd control panel shall be good minute, countdown style with a time entry opion and an adjustable end of cycle audible signal. There shall be 50 minute, including defrost and 4 cooking stages. Microwave output shall be 10 minute, countdown style with a time entry opion and an adjustable end of cycle audible signal. There shall be 50 minute, including defrost and 4 cooking stages. Microwave output shall be 10 minute, countdown style with a time entry opion and an adjustable end of cycle audible signal. There shall be 50 minute, countdown style with a time entry opion and an adjustable end of cycle audible signal.						
CounterCraft Modular Recessed Frost Unit, Quantity Two (2), with FTB 2. Provide counter with cord and plugs. 2014/97/601-2 CounterCraft 2. Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with signometed cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with aminated decor panels with cord/plug. Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP 36" shaft, Heavy Duty, Variable speed Power-1200; 60 Hz; 6.2 Amps This requires a drop-domo outset over a central work table and a wall outlet over the tilt skillet. 24 Commercial Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy duty, 3.75 The commercial moder. 3-speed selection and MAX PULSE to chop and mix Durable, full decast mort housing with nugged nubber feet to reduce vibration. Power-1200; 60 Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Funish and place per palsily to programmable with the sublity to programm						
guard with glass overshelf and lights, 120/15/60hz CounterCraft 2.Person Cashel Unit (ISCL-48-MOO) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with grommeted cut outs for POS cord access, cash drawer with till. Cashler unit to be mobile. Provide unit with laminated decor panels with cord/plug. 23 Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stilk 16" Variable Speed Immersion Blender - 1 HP 16" shaft, Heavy Dutry, Variable speed Power - 1200; 60 Bits, C3 Amps This requires a frop-down outstee over a central work table and a wall outstee over the tilt skillet. 24 Commercial Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Dutry Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full dise-sat motor housing with rugged rubber feet to reduce vibration Power-120Y, 60 Bits, 51 Amps 25 Commercial Microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furnish and place per plans. Commercial microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furnish and place per plans. Commercial microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furnish and place per plans. Commercial microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furnish and place per plans. Commercial microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furnish and place per plans. Commercial microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furnish and place per plans. Commercial microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furnish and place per plans. Commercial microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furnish and place per plans. Commercial microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furnish and place per plans. Commercial Microwave - Manufacturer/Model: Annana Commercial Microwave Model RCS10TS furni						
CounterCraft 2-Person Cashler Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with grommeted uct ust for POS cord access, cash drawer with till. Cashler unit to be mobile. Provide unit with laminated decor panels with cord/plug. Immersion Blender - Manufacturer/Model: Waring WS860 Big Stik 16" Variable Speed Immersion Blender - 1 HP 16" shaft, heavy Duity Variable Speed Prover: 210% 60 Hz. 62 Amps						
grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated decor panels with cord/plug. 23 Immersion Blender - Manufacturer/Model: Waring WS860 Big Stik 16* Variable Speed Immersion Blender - 1 HP 16* shaft, Heavy Duty, Variable speed Power- 120'; 60 Hz, 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. 24 Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 37 Hb Commercial motor As-speed selection and MAX PULSE to chop and mix. Durable, full die-cast notor housing with rugged 1 rubber feet to reduce wibration Power- 120', 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RC510TS Furnish and place per plans Commercial microwave - 10 couch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entity option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watto distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft, 28 littler cavity shall accommodate a 14* (556 mn) platter. Power 120V; 60V; 15 Amp			0			
cord/plug.						
Immersion Blender - Manufacturer/Model: Waring WS860 Big Stik 16" Variable Speed Immersion Blender - 1 HP 16" shaft, Heavy Duty, Variable speed Power: 120V; 60 Hz; 6: 2 Amps 17" Are requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. 24		grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated decor panels with				
10° shaft, Heavy Duty; Variable speed Power - 120V; 60 Hz; 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. 24 Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 He commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cest motor housing with rugged rubber feet to reduce vibration Power - 120V; 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furrish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating to pa natenan to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 • opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 litely cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 50Hz; 15 Amp		cord/plug.				
16" shaft, Heavy Duty, Variable speed Power - 120V; 60 Hz; 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. 24 Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 He Commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full dic-east motor housing with rugged rubber feet to reduce wibration Power - 120V; 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watst distributed by one magnetron with a rotating to pa natenan to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 • opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 lifet) cavity shall accommodate a 14" (35 mm) platter. Power: 120V; 50V; 15 Amp						
16" shaft, Heavy Duty, Variable speed Power - 120V; 60 Hz; 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. 24 Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 He Commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full dic-east motor housing with rugged rubber feet to reduce wibration Power - 120V; 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watst distributed by one magnetron with a rotating to pa natenan to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 • opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 lifet) cavity shall accommodate a 14" (35 mm) platter. Power: 120V; 50V; 15 Amp	22	Immersion Plander, Manufacturer/Model: Waring WCDCO Dig Still 15" Variable Speed Immersion Plander, 1 HD				
Power-120V; 60 Hz; 6: 24 mps This requires a drop-down outset over a central work table and a wall outset over the tilt skillet. 24						
This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet. 24 Commerical Food Bender - Manufacturer/Model: Warring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power-120V;-60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating to pa natenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 a panenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 a polening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 line) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60V; 15 Amp			0			
Commercial Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power- 120V, 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry uption and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V. 60Hz; 155 Amp						
Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power-1200; 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu it kems with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 4 opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity, shall accommodate a 14' (356 mm) platter. Power: 120%, 60Hz; 15 Amp						
3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power- 120v; 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu Items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (35 mm) platter. Power: 120v; 60tt; 15 Amp	24	Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender				
Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power-120ty; 6Dty: 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu litems with two multiple portions. Touch pad shall include Braille for ADA Compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp		Ultra-heavy-duty, 3.75 HP commercial motor				
Durable, full die-cast motor housing with rugged rubber feet to reduce with varion Power- 120V; 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						
rubber feet to reduce vibration Power- 120V; 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall Tacilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp			1			1
Power- 120V; 60Hz; 15 Amps 25 Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						1
Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120Y, 60Hz; 15 Amp						1
Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						
Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp	25	Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS				
Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp		Furnish and place per plans				1
programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						1
items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1,2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						1
Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						1
countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						1
end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						1
be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						
top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						
cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90o + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp		be 1000 watts distributed by one magnetron with a rotating				1
cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90o + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp		top antenna to provide superior even heating throughout the	1			1
a grab and go handle with a 900 + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						1
+ opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						1
interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						
door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						
a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp						1
Power: 120V; 60Hz; 15 Amp						1
						1
Install on a hanging shelf on an open space on the wall.						1
		Install on a hanging shelf on an open space on the wall.		1		1

26	Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with Clear Door - 120V or preapproval alternate	2			
27	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan	15			
28	Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right Hinge Solid Door, 115v or preapproval alternate	2			
29	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan	15			
30	Enclosed Base Worktable Manufacturer Eagle Group Eagle Spec-Master® Enclosed Base Worktable, model OB36*48SE Top is 14/304 stainless steel, sides and back are heavy gauge stainless steel. Open Front 1½" rolled edge on front and rear, sides turned down. Constructed with uni-lok® patented gusset system, with the gussets recessed into the hat channels to reduce lateral movement. 1½" O.D. stainless steel tubular legs with adjustable bullet feet.	2			
31	Worktable Manufacturer Eagle Group Spec-Master* Series Worktable, 72"W x 30"D, 14/300 series stainless steel top, rolled edge on front & back, adjustable 18/300 series stainless steel undershelf with marine edge, Uni-Lok* gusset system, (4) stainless steel legs & adjustable bullet feet, NSF • Model DOS1272-16/4 Overshelf, table mount, 72"W x 12"D x 30"H, double deck, rolled edge on front & rear, turned down sides, 12"H shelf spacing, all-welded 16/430 stainless steel construction, 1" diameter stainless steel tubular base legs, shipped assembled, NSF	1			
32	Worktable Manufacturer Eagle Group Spec-Master® Series Worktable, 72"W x 30"D, 14/300 series stainless steel top, rolled edge on front & back, adjustable 18/300 series stainless steel undershelf with marine edge, Uni-Lok® gusset system, (4) stainless steel legs & adjustable bullet feet, NSF	2			

Mobile Refrigerator (2) and mobile warmer (2) - Both should have sheet pan racks

	IDEA Monterrey Park - 222 SW 35	9th St, San Antonio	o, TX 78237				
Item	Description	Requested Quantity	Brand	Price	Installation Cost Per Unit	Total Cost	Vendor Notes
1	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans, elevations and manufacturer's specifications • Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer • Cover to be stainless steel and hinged with condensate ring • Power pan tilt, tilting console with provision for faucet • Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition • Each unit to be 480V, 3 phase, 60 Hz, 12kw • One Year parts and labor warranty • (2) Faucet bracket assembly • (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer • (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) • (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)	2					
2	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per plans, elevations and manufacturer's specifications. Provide Blodgett full size convection oven model Mark V (double) compartment. Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans. Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous operation. Unit to be electrically heated with three tubular heaters. Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload protection. Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200-500 degrees) with 60 minute timer. Equip units with all standard features available on these units. Double-Deck Provide eall stainless steel 8" legs. Provide vent connector. Warranty; provide Five year limited oven door warranty. One-year parts and labor warranty. Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total	2					

3	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate					
	Regaline Sink, 3-compartment, with left & right-hand drainboards, 24"					
	front-to-back x 24"W sink compartments, 14" deep, with 11"H					
	backsplash, stainless steel legs with welded front-to-rear & adjustable					
	left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel,					
	overall 31" F/B x 106" L/R, NSF	1				
	(requires 2 faucets)					
	1 ea K-453 Control Bracket, 14" x 16" (each)					
	3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections					
	3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain					
	S ea N-4 Support Bracket, for lever waste drain financie, (1) support required for each lever drain					
4	Pre-Rinse Fauce assembly with add on faucet	1				
5	Wall / Splash mount faucet	1				
	Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12	1	-			
6						
	Furnish and set in place per plans, elevations and manufacturer's specifications.					
	Water Filtration System Cartridge for Premium Quality Water					
	• 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing	0				
	• 12 gallon capacity					
	NEMA L6-30P Locking Cap in lieu of NEMA 6-30P					
	• 208V, 1 phase 60 Hz, 24.0A					
7	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.					
	Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.					
	• Sink to be 18" x 24" with 18" drainboards each side.					
	Wash sink compartment to be 11-1/2" deep with 11"H backsplash	1				
	• Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket.	_				
	Add-On-Faucet with 12" swing spout					
	Aud-On-Faucet with 12 Swing Spout					
	D. C. of and another the idea of					
8	Pre-Rinse Faucet assembly with add on faucet	1				
9	Ice Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice Maker, cube-					
	style, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes (not stackable).					
	Refer to MEP for connections					
	• 3 year parts & labor warranty					
	• 5 year parts & labor warranty on evaporator					
	• 5- year parts & 3- year labor warranty on compressor					
	Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter cartridge, (NOT)	1				
	stand-alone; should be used in conjunction with primary water filter assembly)					
	• Ice Bin, 48"W x 34"D, 50"H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice maker,					
	stainless steel exterior, NSF					
	• 6" adjustable stainless steel legs, std.					
10	Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart					
	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• 30" x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf					
	Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
		1				
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides					
1						
11	Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E					
	Furnish and set in place per plans, elevations and manufacturer's specifications	1				
	• Power; 120v,60Hz, 7.6 A.	*				
12	• Power; 120v,buHz, 7.6 A. Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table		 			
12						
	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and under shelf.					
	TA-366 Reinforced understructure for undershelves (maximum					
	recommended load 30 lbs per sq. ft. evenly distributed weight) (each)	1				
	• SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert,					
	stainless steel, with drawer slides					
	Provide with 1-1/2" backsplash					
12			-			
13	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack Furnish and set in place					
	per plans, elevations and manufacturer's specifications					
	Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf.					
	Provide table with one (1) pot rack to be center-mounted to table	1				
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides					

14	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under shelf. Provide One (1) Edlund can opener and mount to table per drawing. Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	1			
15	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	4			
16	Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 Furnish and set in place per plans, elevations and manufacturer's specifications	2			
17	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with hardware, stainless steel • Faucet, splash type, rigid gooseneck, with standard handles • Foot Pedal Valve • Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts • P Trap	3			
18	Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications	3			
19	Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per plans, elevations and manufacturer's specifications	6			
20	Roll-Thru Heated Cabinet, Traulsen Model AlH132LP-FHS or pre-approved alternate Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF, Refer to MEP for connections 1 yr service/labor, 3 yr parts & warranty, standard Thermometer side: Door hinging to be determined Rear: Door hinging to be determined 208V, IP, 60hz Provide New Age 4338 Roll-in Rack at each unit.	2			
21	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-height doors, INTELA-TRAUL™ microprocessor controls. Refer to MEP for connections 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard Thermometer side: Door hinging to be determined Rear: Door hinging to be determined 120V, 1P, 60hz Provide New Age 4338 Roll-in Rack at each unit.	3			
22	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe sneeze guard with glass overshelf and lights. 120V/1P/60hz CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated decor panels with cord/plug.	2			
23	Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP 16" shaft, Heavy Duty; Variable Speed Power- 120V; 60 Hz; 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet.	1			
24	Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power- 120V; 60Hz; 15 Amps	1			

25	Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS				
	Furnish and place per plans				
	Commercial microwave 10 touch pad control panel shall be				
	programmable with the ability to program up to 100 menu				
	items with two multiple portions. Touch pad shall include				
	Braille for ADA compliance. Cooking timer shall be 60 minute,				
	countdown style with a time entry option and an adjustable				
	end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall				
	be 1000 watts distributed by one magnetron with a rotating				
	top antenna to provide superior even heating throughout the	1			
	cavity. Durable door shall have a tempered glass window and				
	a grab and go handle with a 900				
	+ opening for easy access. An				
	interior light shall facilitate monitoring without opening the				
	door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate				
	a 14" (356 mm) platter.				
	Power: 120V; 60Hz; 15 Amp				
	Install on a hanging shelf on an open space on the wall.				
26	Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with Clear Door -	1			
	120V or preapproval alternate	_			
27	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan	15			
28	Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right Hinge Solid Door,	1			
	115v or preapproval alternate				
29	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan	15			

Mobile Refrigerator and mobile warmer - Both should have sheet pan racks

	IDEA Walzem - 6445 Walzem	Rd, San Antonio, T	X 78239				
m	Description	Requested Quantity	Brand	Price	Installation Cost Per Unit	Total Cost	Vendor Notes
1	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans, elevations and manufacturer's specifications Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer Cover to be stainless steel and hinged with condensate ring Power pan tilt, tilting console with provision for faucet Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition Each unit to be 480V, 3 phase, 60 Hz, 12kw One Year parts and labor warranty (2) Faucet bracket assembly (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit)	2					
2	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per plans, elevations and manufacturer's specifications. • Provide Blodgett full size convection oven model Mark V (double) compartment. • Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans. • Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous operation. • Unit to be electrically heated with three tubular heaters. • Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload protection. • Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. • Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60 minute timer. • Equip units with all standard features available on these units. • Double-Deck • Provide all stainless steel 8" legs. • Provide vent connector. • Warranty; provide Five year limited oven door warranty. • One-year parts and labor warranty. • Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total	3					

4 5	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF (requires 2 faucets) 1 ea K-453 Control Bracket, 14" x 16" (each) 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain Pre-Rinse Faucet assembly with add on faucet Wall / Splash mount faucet	1 1 1			
6	Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 Furnish and set in place per plans, elevations and manufacturer's specifications. • Water Filtration System Cartridge for Premium Quality Water • 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing • 12 gallon capacity • NEMA L6-30P Locking Cap in lieu of NEMA 6-30P • 208V, 1 phase 60 Hz, 24.0A	0			
7	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate. Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length. • Sink to be 18" x 24" with 18" drainboards each side. • Wash sink compartment to be 11-1/2" deep with 11"H backsplash • Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket. • Add-On-Faucet with 12" swing spout	1			
8	Pre-Rinse Faucet assembly with add on faucet	1			
9	lce Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice Maker, cubestyle, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes (not stackable). • Refer to MEP for connections • 3 year parts & labor warranty • 5 year parts & labor warranty on evaporator • 5- year parts & 3- year labor warranty on compressor • Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter cartridge, (NOT stand-alone; should be used in conjunction with primary water filter assembly) • Ice Bin, 48"W x 34"D, 50"H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice maker, stainless steel exterior, NSF • 6" adjustable stainless steel legs, std.	1			
10	Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart Furnish and set in place per plans, elevations and manufacturer's specifications • 30" x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	1			
11	Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E Furnish and set in place per plans, elevations and manufacturer's specifications • Power; 120v,60Hz, 7.6 A.	1			
12	Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and under shelf. • TA-366 Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides • Provide with 1-1/2" backsplash	1			
13	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf. • Provide table with one (1) pot rack to be center-mounted to table • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	1			

14	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under shelf. • Provide One (1) Edlund can opener and mount to table per drawing. • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	1			
15	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications • Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides	4			
16	Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 Furnish and set in place per plans, elevations and manufacturer's specifications	1			
17	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal Hand Sink wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with hardware, stainless steel • Faucet, splash type, rigid gooseneck, with standard handles • Foot Pedal Valve • Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts • P Trap	4			
18	Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications	4			
19	Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per plans, elevations and manufacturer's specifications	10			
20	Roll-Thru Heated Cabinet - Traulsen Model AlH132LP-FHS or pre-approved alternate Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF, Refer to MeP for connections 1 yr service/labor, 3 yr parts & warranty, standard Thermometer side: Door hinging to be determined Rear: Door hinging to be determined 2 208V, 1P, 60hz Provide New Age 4338 Roll-in Rack at each unit.	2			
21	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-height doors, INTELA-TRAUL™ microprocessor controls. • Refer to MeP for connections • 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard • Thermometer side: Door hinging to be determined • Rear: Door hinging to be determined • 120V, 1P, 60hz • Provide New Age 4338 Roll-in Rack at each unit.	3			
22	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-5 Built-in Heated Shelf. Provide counter with integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe sneeze guard with glass overshelf and lights. 120V/1P/60hz CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated decor panels with cord/plug.	2			
23	Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP 16" shaft, Heavy Duty; Variable speed Power- 120V; 60 Hz; 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet.	1			
24	Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power- 120V; 60Hz; 15 Amps	1			

25	Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS				
	Furnish and place per plans				
	Commercial microwave 10 touch pad control panel shall be				
	programmable with the ability to program up to 100 menu				
	items with two multiple portions. Touch pad shall include				
	Braille for ADA compliance. Cooking timer shall be 60 minute,				
	countdown style with a time entry option and an adjustable				
	end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall				
	be 1000 watts distributed by one magnetron with a rotating				
	top antenna to provide superior even heating throughout the	1			
	cavity. Durable door shall have a tempered glass window and				
	a grab and go handle with a 900				
	+ opening for easy access. An				
	interior light shall facilitate monitoring without opening the				
	door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate				
	a 14" (356 mm) platter.				
	Power: 120V; 60Hz; 15 Amp				
	Install on a hanging shelf on an open space on the wall.				
26	Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with Clear Door -	1			
	120V or preapproval alternate				
27	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan	15			
28	Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right Hinge Solid Door,	1			
	115v or preapproval alternate				
29	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan	15			

Mobile Refrigerator and mobile warmer - Both should have sheet pan racks

Buy Out Optional							
Estimated		Unit Buy Out					
Quantity	Description	Price	Total Buy Out Price				
9	Tilting skillet						
11	Convection Oven						
4	3 Compartment Sink						
4	Pre-Rinse Faucet assembly with add on faucet						
4	Wall / Splash mount faucet						
1	Hot Water Dispenser						
4	Two Compartment Sink						
4	Pre-Rinse Faucet assembly with add on faucet						
4	Ice Maker and Bin						
4	Work Table/ Cart						
4	Food Processor						
4	Work Table						
5	Work Table w/ Pot Rack						
4	Work Table w/ drawers and can opener						
16	Work Table w/ drawers						
4	Mobile Pan Rack						
12	Hand Sink						
15	Utility Cart						
36	Refrigerator Rack, Roll-in						
16	Roll-Thru Heated Cabinet						
10	Roll-Thru Refrigerator Cabinet						
6	Serving Counter						
3	Immersion Blender						
4	Commercial Food Blender						
4	Commercial Microwave						
6	Mobile Heated Holding						
60	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan						
6	Mobile Cooling Holding						
60	Choice Full Size 18" x 26" 19 Gauge Wire in Rim Aluminum Bun Pan / Sheet Pan						
4	Reach-In Display Refrigerator						
2	Enclosed Base Worktable						
1	Worktable w/ Overshelf						
2	Worktable w/ Undershelf						