

EQUIPMENT PRICING TEMPLATE RFP #17-CNPKFL-0424

Vendor Information All Specification are provided on manufacturer description. The awarded vendor is responsible to ensure that equipment meets the space needs of the identified campus.

IDEA Donna - 401 S 1st St, Donna, TX 7853							
Item	Description	Requested Quantity	Brand	Price	Installation Cost Per Unit	Total Cost	Vendor Notes
1	<p>Tilting Skillet - Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer Cover to be stainless steel and hinged with condensate ring Power pan tilt, tilting console with provision for faucet Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition Each unit to be 480V, 3 phase, 60 Hz, 12kw One Year parts and labor warranty (2) Faucet bracket assembly (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit) 	3					
2	<p>Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per plans, elevations and manufacturer's specifications.</p> <ul style="list-style-type: none"> Provide Blodgett full size convection oven model Mark V (double) compartment. Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans. Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous operation. Unit to be electrically heated with three tubular heaters. Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload protection. Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60 minute timer. Equip units with all standard features available on these units. Double-Deck Provide all stainless steel 8" legs. Provide vent connector. Warranty; provide Five year limited oven door warranty. One-year parts and labor warranty. Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total 	4					
3	<p>3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF (requires 2 faucets)</p> <p>1 ea K-453 Control Bracket, 14" x 16" (each) 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain</p>	1					
4	Pre-Rinse Faucet assembly with add on faucet	1					
5	Wall / Splash mount faucet	1					
6	<p>Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12</p> <p>Furnish and set in place per plans, elevations and manufacturer's specifications.</p> <ul style="list-style-type: none"> Water Filtration System Cartridge for Premium Quality Water 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing 12 gallon capacity NEMA LG-30P Locking Cap in lieu of NEMA 6-30P 208V, 1 phase 60 Hz, 24.0A 	1					
7	<p>Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.</p> <p>Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.</p> <ul style="list-style-type: none"> Sink to be 18" x 24" with 18" drainboards each side. Wash sink compartment to be 11-1/2" deep with 11"H backsplash Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket. Add-On-Faucet with 12" swing spout 	1					
8	Pre-Rinse Faucet assembly with add on faucet	1					

Vendor / Contractor Name:

Invalid if installation cost field is not populated

9	<p>Ice Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice Maker, cube-style, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes (not stackable).</p> <ul style="list-style-type: none"> • Refer to MEP for connections • 3 year parts & labor warranty • 5 year parts & labor warranty on evaporator • 5- year parts & 3- year labor warranty on compressor • Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter cartridge, (NOT stand-alone; should be used in conjunction with primary water filter assembly) • Ice Bin, 48"W x 34"D, 50"H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice maker, stainless steel exterior, NSF • 6" adjustable stainless steel legs, std. 	1					
10	<p>Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart</p> <p>Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> • 30"x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	1					
11	<p>Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E</p> <p>Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> • Power; 120v,60Hz, 7.6 A. 	1					
12	<p>Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table</p> <p>Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> • Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and under shelf. • TA-366 Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides • Provide with 1-1/2" backsplash 	1					
13	<p>Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack</p> <p>Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> • Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf. • Provide table with one (1) pot rack to be center-mounted to table 36" x 96" • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	2					
14	<p>Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table</p> <p>Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> • Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under shelf. • Provide One (1) Edlund can opener and mount to table per drawing. • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	1					
15	<p>Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table</p> <p>Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> • Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	4					
16	<p>Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448</p> <p>Furnish and set in place per plans, elevations and manufacturer's specifications</p>	1					

17	<p>Hand Sink - IMC/Teddy Model CSW-25 or pre-approved equal Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with hardware, stainless steel</p> <ul style="list-style-type: none"> • Faucet, splash type, rigid gooseneck, with standard handles • Foot Pedal Valve • Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts • P Trap 	3					
18	Utility Carb - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications	4					
19	Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per plans, elevations and manufacturer's specifications	10					
20	<p>Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,</p> <ul style="list-style-type: none"> • Refer to MEP for connections • 1 yr service/labor, 3 yr parts & warranty, standard • Thermometer side: Door hinging to be determined • Rear: Door hinging to be determined • 208V, 1P, 60hz • Provide New Age 4338 Roll-in Rack at each unit. 	6					
21	<p>Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-height doors, INTELA-TRAUL™ microprocessor controls.</p> <ul style="list-style-type: none"> • Refer to MEP for connections • 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard • Thermometer side: Door hinging to be determined • Rear: Door hinging to be determined • 120V, 1P, 60hz • Provide New Age 4338 Roll-in Rack at each unit. 	4					
22	<p>Serving Counter - CounterCraft Model SERVING COUNTER or pre-approved alternate CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe sneeze guard with glass overshef and lights. 120V/1P/60hz CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated decor panels with cord/plug.</p>	2					
23	<p>Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP 16" shaft, Heavy Duty; Variable speed Power- 120V; 60 Hz; 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet.</p>	1					
24	<p>Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power- 120V; 60Hz; 15 Amps</p>	1					

25	Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90o + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp Install on a hanging shelf on an open space on the wall.	1					
26	Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with Clear Door - 120V or preapproval alternate	2					
27	Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right Hinge Solid Door, 115v or preapproval alternate	2					

Mobile Refrigerator (2) and mobile warmer (2) - Both should have sheet pan racks

IDEA Weslaco Pike - 1000 E Pike Blvd, Weslaco TX 78596							
Item	Description	Requested Quantity	Brand	Price	Installation Cost Per Unit	Total Cost	Vendor Notes
1	Tilting Skillet- TILTING SKILLET BRAISING PAN, ELECTRIC (2 REQ'D) Vulcan Model VE40 Dimensions: 40.5(h) x 46(w) x 35.5(d) Braising Pan, electric, 40-gallon capacity, 16 kW FastBatch™ embedded heating technology, 46" wide open base, manual tilt, 9" deep stainless steel pan with gallon markings, pouring lip & removable strainer, spring assist cover with drip edge, pan holder, water tight solid state controls, includes L faucet bracket, 12" stainless steel legs with adjustable flanged feet, cULus, UL EPH Classified 2 ea - 1 year limited parts & labor warranty, standard 2 ea - K-12 School Nutrition extended warranty extends the warranty for 12 months beyond the 12 month Original Equipment Warranty, not to exceed 24 months from date of installation 2 ea - 480v/60/3-ph, 16 kW, 20.0 amps, direct wire 2 ea - Model SGLTS 12NzL SINGLE Pantry Deck-Mount Faucet, 12" swivel spout, includes 4" & 12" riser, NSF & Lead Reduction Compliant (Note: water connection required)	2					
2	Convection Oven - CONVECTION OVEN, ELECTRIC (2 REQ'D) Vulcan Model VC44ED Dimensions: 70(h) x 40(w) x 42.25(d) Convection Oven, electric, double-deck, standard depth, solid state controls, temperature range 150° to 500°F, 60 minute timer with audible alarm per oven, oven cool switch for rapid cool down, independently operated stainless steel doors with double pane windows, porcelain enamel on steel oven interiors, (5) nickel plated racks per oven, stainless steel front, top, sides & 8"H legs, (2) 1/2 HP two speed oven blower-motors, 12 kW each section, NSF, cUL, UL, ENERGY STAR® 2 ea - 1 year limited parts & labor warranty, standard 2 ea - K-12 School Nutrition extended warranty extends the warranty for 12 months beyond the 12 month Original Equipment Warranty, not to exceed 24 months from date of installation 4 ea - (2) 480v/60/3-ph, 30 amps total, priced per oven 4 ea - Simultaneous doors, both ovens 2 ea - SST legs, standard	2					

3	3 Compartment Sink - Three-Compartment Sink - Manufacturer/Model: Eagle Group Model FN2060-3-18-14/3-TB, or pre- approved alternate. Eagle Spec-Master® Three-Compartment Sinks. Unit constructed of 14-gauge 300 series, 18-8 stainless steel throughout. Sink bowls covered with a full ½" radius and shall have a 14" high water level and requires 2 faucets. Overall dimensions 27" deep, 102" long. Left & right-hand 18" drainboards "V" creased for positive drainage. 9½" high backsplash with 1" upturn and tile edge. Legs to be 1½" O.D., stainless steel, with stainless steel gussets, stainless steel crossbracing and adjustable stainless steel bullet feet. <ul style="list-style-type: none"> • 18" undershelves left and right under drainboards. • Mount Cantilever Shelf Through Splash left and right with 24" overshelf • Three (3) each TB Support Bracket, for lever waste drain handle. • Three (3) each 341189 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 	1					
4	B-0133-16-B08EL T&S Pre-Rinse, Spring Action, 8" Wall Mount, 16" Add-On, Wall Bracket, B-0108 Spray Valve.	1					
5	B-0230-02 8" T&S Wall Mount Base Faucet, 18" Swing Nozzle, 2.2 GPM Aerator, Lever Handles	1					
6	Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 Furnish and set in place per plans, elevations and manufacturer's specifications. <ul style="list-style-type: none"> • Water Filtration System Cartridge for Premium Quality Water • 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing • 12 gallon capacity • NEMA L6-30P Locking Cap in lieu of NEMA 6-30P • 208V, 1 phase 60 Hz, 24.0A 	0					
7	Two Compartment Sink - Two-Compartment Sink - Manufacturer/Model: Eagle Group Model FN2032-2-18-14/3-TB, or pre- approved alternate. Eagle Spec-Master® Two-Compartment Sinks. Unit constructed of 14-gauge 300 series, 18-8 stainless steel throughout. Sink bowls covered with a full ½" radius and shall have a 14" high water level and requires 2 faucets. Bowls are 16" wide, 20" front-to-back, 14" deep compartments. Overall dimensions 27" deep, 72" long. <ul style="list-style-type: none"> • Left & right-hand drainboards 18" Drainboards shall be "V" creased for positive drainage. 9½" high backsplash with 1" upturn and tile edge. Legs to be 1½" O.D., stainless steel, with stainless steel gussets, stainless steel crossbracing and adjustable stainless steel bullet feet. • 18" undershelves left and right under drainboards. • Two (2) each TB Support Bracket, for lever waste drain handle. • Two (2) each 341189 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections. • One (1) each B-0133-16-B08EL Pre-Rinse, Spring Action, 8" Wall Mount, 16" Add-On, Wall Bracket, B-0108 Spray Valve. • One (1) each B-0230-02 8" Wall Mount Base Faucet, 18" Swing Nozzle, 2.2 GPM Aerator, Lever Handles 	1					
8	Pre-Rinse Faucet assembly with add on faucet	1					
9	Ice Maker & Bin - The Manitowoc Ice IYT-0420A-161/D-420 Indigo NXT™ ice maker with bin can provide a 460-pound maximum daily output. Ice thickness is measured by an acoustical sensing probe, ensuring each cycle is uniform. Through the control system, preventive maintenance provides users with diagnostic feedback. If there is an issue in the foodzone, the operator can easily access the area through the swing-out front door. This access design also simplifies cleanup, and some of the parts are removable and made with AlphaSan® antimicrobial. Weight 136 Width 22 Depth 25 Height 22 Voltage and faces	1					
10	Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E Furnish and set in place per plans, elevations and manufacturer's specifications <ul style="list-style-type: none"> • Power; 120v,60Hz, 7.6 A. 	1					
11	Worktable Manufacturer Eagle Group Spec-Master® Series Worktable, 72"W x 30"D, 14/300 series stainless steel top, rolled edge on front & back, adjustable 18/300 series stainless steel undershelf with marine edge, Uni-Lok® gusset system, (4) stainless steel legs & adjustable bullet feet, NSF <ul style="list-style-type: none"> • Model TM72PR Pot Rack, table mount, 64"W x 20"D, triple-bar design with tubular table supports, constructed of 3/16" x 2" stainless steel flat bar, includes (18) double-pronged pot hooks, for 72"W table, NSF 	1					
12	Hand Sink - IMC/Teddy Model CSW-25 or pre-approved equal Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with hardware, stainless steel <ul style="list-style-type: none"> • Faucet, splash type, rigid gooseneck, with standard handles • Foot Pedal Valve • Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts • P Trap 	2					
13	Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications	4					

Vendor / Contractor Name:

Invalid if installation cost field is not populated

14	REFRIGERATOR/FREEZER RACK, ROLL-IN New Age Model 4338 Dimensions: 64(h) x 21.5(w) x 26(d) Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing (non-adjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights, (4) 5" platform swivel casters, NSF, Made in USA, (standard factory lead time) 10 ea - Lifetime guarantee against rust & corrosion. Lifetime guarantee against workmanship and material defects.	10					
15	Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF, • Refer to MEP for connections • 1 yr service/labor, 3 yr parts & warranty, standard • Thermometer side: Door hinging to be determined • Rear: Door hinging to be determined • 208V, 1P, 60hz • Provide New Age 4338 Roll-in Rack at each unit.	6					
16	REACH-IN DISPLAY REFRIGERATOR, 1 SECTION Traulsen Model AHT132WUT-FHG Dimensions: 83.25(h) x 29.88(w) x 35(d) Spec-Line Refrigerator, Reach-in Display, one-section, 24.2 cu. ft., self-contained refrigeration, StayClear™ Condenser, stainless steel exterior, aluminum interior, standard depth, wide full-height glass door or doors with EZ-Clean Gaskets, interior lights, (3) adjustable wire shelves per section, microprocessor controls, 6" adjustable stainless steel legs, 1/3 HP, cULus, NSF 4 ea - 6-year parts & labor and 7 year compressor, standard. Visit www.traulsen.com for details 4 ea - 115v/60/1-ph, 8.0 amps, with cord & NEMA 5-15P, standard 4 ea - Standard refrigerant, standard 4 ea - Door hinged on right, standard 52 ea - Universal tray slides for (1) 18"x26" or (2) 14"x18" or (2) 12" x 20" pans -per pair 12 ea - Credit for standard coated shelf, deduct 4 st - Casters, 6" high (set of 4)	4					
17	Commercial Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power: 120V; 60Hz; 15 Amps	1					
18	Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90o + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp Install on a hanging shelf on an open space on the wall.	1					
19	Enclosed Base Worktable Manufacturer Eagle Group Eagle Spec-Master® Enclosed Base Worktable, model OB36*48SE Top is 14/304 stainless steel, sides and back are heavy gauge stainless steel. Open Front 1½" rolled edge on front and rear, sides turned down. Constructed with uni-lok® patented gusset system, with the gussets recessed into the hat channels to reduce lateral movement. 1½" O.D. stainless steel tubular legs with adjustable bullet feet.	2					
20	Worktable Manufacturer Eagle Group Spec-Master® Series Worktable, 72"W x 30"D, 14/300 series stainless steel top, rolled edge on front & back, adjustable 18/300 series stainless steel undershelf with marine edge, Uni-Lok® gusset system, (4) stainless steel legs & adjustable bullet feet, NSF • Model DOS1272-16/4 Overshelf, table mount, 72"W x 12"D x 30"H, double deck, rolled edge on front & rear, turned down sides, 12"H shelf spacing, all-welded 16/430 stainless steel construction, 1" diameter stainless steel tubular base legs, shipped assembled, NSF	1					

21	Worktable Manufacturer Eagle Group Spec-Master® Series Worktable, 72"W x 30"D, 14/300 series stainless steel top, rolled edge on front & back, adjustable 18/300 series stainless steel undershelf with marine edge, Uni-Lok® gusset system, (4) stainless steel legs & adjustable bullet feet, NSF	2					
----	---	---	--	--	--	--	--

Mobile Refrigerator (2) and mobile warmer (2) - Both should have sheet pan racks

IDEA Monterrey Park - 222 SW 39th St, San Antonio, TX 78237							
Item	Description	Requested Quantity	Brand	Price	Installation Cost Per Unit	Total Cost	Vendor Notes
1	Tilting Skillet - Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans, elevations and manufacturer's specifications <ul style="list-style-type: none"> Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer Cover to be stainless steel and hinged with condensate ring Power pan tilt, tilting console with provision for faucet Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition Each unit to be 480V, 3 phase, 60 Hz, 12kw One Year parts and labor warranty (2) Faucet bracket assembly (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit) 	2					
2	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per plans, elevations and manufacturer's specifications. <ul style="list-style-type: none"> Provide Blodgett full size convection oven model Mark V (double) compartment. Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans. Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous operation. Unit to be electrically heated with three tubular heaters. Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload protection. Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60 minute timer. Equip units with all standard features available on these units. Double-Deck Provide all stainless steel 8" legs. Provide vent connector. Warranty; provide Five year limited oven door warranty. One-year parts and labor warranty. Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total 	2					
3	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF (requires 2 faucets) 1 ea K-453 Control Bracket, 14" x 16" (each) 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain	1					
4	Pre-Rinse Fauce assembly with add on faucet	1					
5	Wall / Splash mount faucet	1					
6	Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 Furnish and set in place per plans, elevations and manufacturer's specifications. <ul style="list-style-type: none"> Water Filtration System Cartridge for Premium Quality Water 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing 12 gallon capacity NEMA L6-30P Locking Cap in lieu of NEMA 6-30P 208V, 1 phase 60 Hz, 24.0A 	0					
7	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate. Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length. <ul style="list-style-type: none"> Sink to be 18" x 24" with 18" drainboards each side. Wash sink compartment to be 11-1/2" deep with 11"H backsplash Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket. Add-On-Faucet with 12" swing spout 	1					

Vendor / Contractor Name:

Invalid if installation cost field is not populated

8	Pre-Rinse Faucet assembly with add on faucet	1					
9	Ice Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice Maker, cube-style, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes (not stackable). <ul style="list-style-type: none"> Refer to MEP for connections 3 year parts & labor warranty 5 year parts & labor warranty on evaporator 5- year parts & 3- year labor warranty on compressor Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter cartridge, (NOT stand-alone; should be used in conjunction with primary water filter assembly) Ice Bin, 48"W x 34"D, 50"H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice maker, stainless steel exterior, NSF 6" adjustable stainless steel legs, std. 	1					
10	Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart Furnish and set in place per plans, elevations and manufacturer's specifications <ul style="list-style-type: none"> 30"x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	1					
11	Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E Furnish and set in place per plans, elevations and manufacturer's specifications <ul style="list-style-type: none"> Power; 120v,60Hz, 7.6 A. 	1					
12	Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications <ul style="list-style-type: none"> Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and under shelf. TA-366 Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides Provide with 1-1/2" backsplash 	1					
13	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack Furnish and set in place per plans, elevations and manufacturer's specifications <ul style="list-style-type: none"> Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf. Provide table with one (1) pot rack to be center-mounted to table Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	1					
14	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications <ul style="list-style-type: none"> Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under shelf. Provide One (1) Edlund can opener and mount to table per drawing. Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	1					
15	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications <ul style="list-style-type: none"> Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	4					
16	Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 Furnish and set in place per plans, elevations and manufacturer's specifications	2					

17	<p>Hand Sink - IMC/Teddy Model CSW-25 or pre-approved equal Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with hardware, stainless steel</p> <ul style="list-style-type: none"> • Faucet, splash type, rigid gooseneck, with standard handles • Foot Pedal Valve • Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts • P Trap 	3					
18	Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications	3					
19	Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per plans, elevations and manufacturer's specifications	6					
20	<p>Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,</p> <ul style="list-style-type: none"> • Refer to MEP for connections • 1 yr service/labor, 3 yr parts & warranty, standard • Thermometer side: Door hinging to be determined • Rear: Door hinging to be determined • 208V, 1P, 60hz • Provide New Age 4338 Roll-in Rack at each unit. 	2					
21	<p>Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-height doors, INTELA-TRAUL™ microprocessor controls.</p> <ul style="list-style-type: none"> • Refer to MEP for connections • 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard • Thermometer side: Door hinging to be determined • Rear: Door hinging to be determined • 120V , 1P, 60hz • Provide New Age 4338 Roll-in Rack at each unit. 	3					
22	<p>Serving Counter - CounterCraft Model SERVING COUNTER or pre-approved alternate CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe sneeze guard with glass overshef and lights. 120V/1P/60hz CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with grommetted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated decor panels with cord/plug.</p>	2					
23	<p>Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP 16" shaft, Heavy Duty; Variable speed Power- 120V; 60 Hz; 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet.</p>	1					
24	<p>Commerical Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power- 120V; 60Hz; 15 Amps</p>	1					

25	<p>Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS</p> <p>Furnish and place per plans</p> <p>Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90o + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter.</p> <p>Power: 120V; 60Hz; 15 Amp</p> <p>Install on a hanging shelf on an open space on the wall.</p>	1					
26	<p>Mobile Heated Holding - Manufacturer/Model No. Avanco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with Clear Door - 120V or preapproval alternate</p>	1					
27	<p>Mobile Cooling Holding - Manufacturer/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right Hinge Solid Door, 115v or preapproval alternate</p>	1					

Mobile Refrigerator and mobile warmer - Both should have sheet pan racks

IDEA Walzem - 6445 Walzem Rd, San Antonio, TX 78239							
Item	Description	Requested Quantity	Brand	Price	Installation Cost Per Unit	Total Cost	Vendor Notes
1	<p>Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer Cover to be stainless steel and hinged with condensate ring Power pan tilt, tilting console with provision for faucet Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition Each unit to be 480V, 3 phase, 60 Hz, 12kw One Year parts and labor warranty (2) Faucet bracket assembly (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit) (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit) 	2					
2	<p>Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per plans, elevations and manufacturer's specifications.</p> <ul style="list-style-type: none"> Provide Blodgett full size convection oven model Mark V (double) compartment. Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans. Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous operation. Unit to be electrically heated with three tubular heaters. Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload protection. Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks. Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60 minute timer. Equip units with all standard features available on these units. Double-Deck Provide all stainless steel 8" legs. Provide vent connector. Warranty; provide Five year limited oven door warranty. One-year parts and labor warranty. Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total 	3					

3	<p>3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable left-to-right cross rails, 3/6" drainboards, 1" adjustable bullet feet, 14-gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF (requires 2 faucets) 1 ea K-453 Control Bracket, 14" x 16" (each) 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain</p>	1					
4	Pre-Rinse Faucet assembly with add on faucet	1					
5	Wall / Splash mount faucet	1					
6	<p>Hot Water Dispenser - Manufacturer/Model: Hatco AWD-12 Furnish and set in place per plans, elevations and manufacturer's specifications.</p> <ul style="list-style-type: none"> Water Filtration System Cartridge for Premium Quality Water 3' (914 mm) Rubber Drain Hose with 10' (3048 mm) 1/4" Inlet Tubing 12 gallon capacity NEMA L6-30P Locking Cap in lieu of NEMA 6-30P 208V, 1 phase 60 Hz, 24.0A 	0					
7	<p>Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate. Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.</p> <ul style="list-style-type: none"> Sink to be 18" x 24" with 18" drainboards each side. Wash sink compartment to be 11-1/2" deep with 11"H backsplash Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket. Add-On-Faucet with 12" swing spout 	1					
8	Pre-Rinse Faucet assembly with add on faucet	1					
9	<p>Ice Maker & Bin - Manufacturer/Model: Manitowoc Model ID-0906A / B970 Bin or pre-approved alternate Indigo™ Series Ice Maker, cube-style, air-cooled, self-contained condenser, up to 901-lb approximately/24 hours, stainless steel finish, dice size cubes (not stackable).</p> <ul style="list-style-type: none"> Refer to MEP for connections 3 year parts & labor warranty 5 year parts & labor warranty on evaporator 5- year parts & 3- year labor warranty on compressor Arctic Pure® Pre-Filter Assembly, 5 micron filtration includes head, shroud, hardware, mounting assembly, and one filter cartridge, (NOT stand-alone; should be used in conjunction with primary water filter assembly) Ice Bin, 48"W x 34"D, 50"H, with top-hinged front-opening door, AHRI certified 710 lb ice storage capacity, for top-mounted ice maker, stainless steel exterior, NSF 6" adjustable stainless steel legs, std. 	1					
10	<p>Work Table / Cart - Manufacturer/Model: CounterCraft Lite Model Prep Table/Cart Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> 30"x 30" Work table, top flat top, constructed of 14-gauge stainless steel with 8" locking casters, drawer and under shelf Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	1					
11	<p>Food Processor - Manufacturer/Model: Robot Coupe No. CL50 Ultra E Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> Power; 120v, 60Hz, 7.6 A. 	1					
12	<p>Work Table - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> Work table, 30"x72" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, Three (3) drawer and under shelf. TA-366 Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) SS-1520 Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides Provide with 1-1/2" backsplash 	1					

13	<p>Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with center-mounted Pot Rack Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> • Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf. • Provide table with one (1) pot rack to be center-mounted to table • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	1					
14	<p>Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> • Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under shelf. • Provide One (1) Edlund can opener and mount to table per drawing. • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	1					
15	<p>Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table Furnish and set in place per plans, elevations and manufacturer's specifications</p> <ul style="list-style-type: none"> • Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs • Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each) • 16 gauge 304 series stainless steel undershelf upgrade (per linear foot) • 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides 	4					
16	<p>Mobile Pan Rack - Manufacturer/Model: New Age Industrial Corp. No. PM2448 Furnish and set in place per plans, elevations and manufacturer's specifications</p>	1					
17	<p>Hand Sink - IMC/Teddy Model CSW-25 or pre-approved equal Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with hardware, stainless steel</p> <ul style="list-style-type: none"> • Faucet, splash type, rigid gooseneck, with standard handles • Foot Pedal Valve • Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts • P Trap 	4					
18	<p>Utility Cart - Rubbermaid FG409100BLA Furnish and set in place per plans, elevations and manufacturer's specifications</p>	4					
19	<p>Refrigerator Rack, Roll-in - Manufacturer/Model: New Age Industrial Corp. Lifetime Series No. 4338 Furnish and set in place per plans, elevations and manufacturer's specifications</p>	10					
20	<p>Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,</p> <ul style="list-style-type: none"> • Refer to MEP for connections • 1 yr service/labor, 3 yr parts & warranty, standard • Thermometer side: Door hinging to be determined • Rear: Door hinging to be determined • 208V, 1P, 60hz • Provide New Age 4338 Roll-in Rack at each unit. 	2					
21	<p>Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-height doors, INTELA-TRAUL™ microprocessor controls.</p> <ul style="list-style-type: none"> • Refer to MEP for connections • 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard • Thermometer side: Door hinging to be determined • Rear: Door hinging to be determined • 120V, 1P, 60hz • Provide New Age 4338 Roll-in Rack at each unit. 	3					
22	<p>Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe sneeze guard with glass overshelf and lights. 120V/1P/60hz CounterCraft 2-Person Cashier Unit (SCSL-48-MOD) with stainless steel tray slides of both sides of unit on fixed brackets. Provide unit with grommeted cut outs for POS cord access, cash drawer with till. Cashier unit to be mobile. Provide unit with laminated decor panels with cord/plug.</p>	2					

Vendor / Contractor Name:

Invalid if installation cost field is not populated

23	Immersion Blender - Manufacturer/Model: Waring WSB60 Big Stik 16" Variable Speed Immersion Blender - 1 HP 16" shaft, Heavy Duty; Variable speed Power- 120V; 60 Hz; 6.2 Amps This requires a drop-down outlet over a central work table and a wall outlet over the tilt skillet.	1				
24	Commercial Food Blender - Manufacturer/Model: Waring Model No. CB15P - 1 Gallon Heavy Duty Blender Ultra-heavy-duty, 3.75 HP commercial motor 3-speed selection and MAX PULSE to chop and mix Durable, full die-cast motor housing with rugged rubber feet to reduce vibration Power- 120V; 60Hz; 15 Amps	1				
25	Commercial Microwave - Manufacturer/Model: Amana Commercial Microwave Model RCS10TS Furnish and place per plans Commercial microwave 10 touch pad control panel shall be programmable with the ability to program up to 100 menu items with two multiple portions. Touch pad shall include Braille for ADA compliance. Cooking timer shall be 60 minute, countdown style with a time entry option and an adjustable end of cycle audible signal. There shall be 5 power levels, including defrost and 4 cooking stages. Microwave output shall be 1000 watts distributed by one magnetron with a rotating top antenna to provide superior even heating throughout the cavity. Durable door shall have a tempered glass window and a grab and go handle with a 90o + opening for easy access. An interior light shall facilitate monitoring without opening the door. The large 1.2 cubic ft. (34 liter) cavity shall accommodate a 14" (356 mm) platter. Power: 120V; 60Hz; 15 Amp Install on a hanging shelf on an open space on the wall.	1				
26	Mobile Heated Holding - Manufacturer/Model No. Avantco HPI-1836 Full Size Insulated Heated Holding / Proofing Cabinet with Clear Door - 120V or preapproval alternate	1				
27	Mobile Cooling Holding - Manufacturere/Model No: MoTak MSD-1DR-BAL 29" One Section Reach In Refrigerator, (1) Right Hinge Solid Door, 115v or preapproval alternate	1				

Mobile Refrigerator and mobile warmer - Both should have sheet pan racks

Buy Out Optional		
Estimated Qty.	Description	Total Buy Out Price
9	Tilting skillet	
11	Convection Oven	
4	3 Compartment Sink	
4	Pre-Rinse Faucet assembly with add on faucet	
4	Wall / Splash mount faucet	
1	Hot Water Dispenser	
4	Two Compartment Sink	
4	Pre-Rinse Faucet assembly with add on faucet	
4	Ice Maker and Bin	
3	Work Table/ Cart	
4	Food Processor	
4	Work Table	
5	Work Table w/ Pot Rack	
3	Work Table w/ drawers and can opener	
12	Work Table w/ drawers	
1	Work Table w/ Overshelf	
1	Enclosed Base Worktable	
4	Mobile Pan Rack	
12	Hand Sink	
15	Utility Cart	
1	Reach-In Display Refrigerator	
36	Refrigerator Rack, Roll-in	
16	Roll-Thru Heated Cabinet	
10	Roll-Thru Refrigerator Cabinet	
6	Serving Counter	
3	Immersion Blender	
4	Commercial Food Blender	
4	Commercial Microwave	
4	Mobile Heated Holding	
4	Mobile Cooling Holding	

Vendor / Contractor Name:

Invalid if installation cost field is not populated