

02-RFP-CNP-2122: Kitchen Facelifts Due: Feb. 17th, 2022 @ 2:00 PM

RANKING CRITERIA	TARI dba Jeans Restaurant Supply
	Average scores
Proposed price under this program: Proposed price under this program.	50
2. The responsiveness of the vendor: The vendor provided all documentation requested in the RFP	8.3
3. The reputation of the vendor and of the vendor's goods and services: The respondent's experience and demonstrated competence with similar type of services with districts and/or public entities	9.4
4. The vendor's past relationship with other educational institutions: The respondent's type of services provided to other organizations based on the verified reference forms submitted	4.8
5. The vendor's Warranty and warranty service history: The vendor's warranty history based on the verified reference forms submitted	14.4
6.Meets Completion Schedule Timeline: Delivery schedule of equipment and completion of labor at each campus is met	9.2
Average Score	96.13



02-RFP-CNP-2122 Kitchen Facelift Pricing

Vendor Information	All specificaations are provided based on manufacturer description. The awareded vendor					
	is responsible to ensure that equipment meets the space needs of the identified campus					
				TARI dba Jean	s Restaurant Sup	ply
DEA Alamo						
em	Description	Quantity	Quantity Jeans	Price	Total Cost	Vendor notes
onvection Oven	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per	6				
	plans, elevations and manufacturer's specifications.					
	Provide Blodgett full size convection oven model Mark V (double) compartment.					
	• Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans.					
	• Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous					
	operation.					
	• Unit to be electrically heated with three tubular heaters.					
	• Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload					
	protection.					
	• Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks.					
	• Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60					
	minute timer.					
	Equip units with all standard features available on these units. Double-Deck					
	Provide all stainless steel 8" legs.					
	Provide vent connector.					
	Warranty; provide Five year limited oven door warranty.					
	One-year parts and labor warranty.					
	• Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total		6	13087.01	78522.06	
ILTING SKILLET BRAISING PAN, ELECTRIC	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans,	2			7 0022.00	
,	elevations and manufacturer's specifications	_				
	• Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer					
	Cover to be stainless steel and hinged with condensate ring					
	Power pan tilt, tilting console with provision for faucet					
	• Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition					
	• Each unit to be 480V, 3 phase, 60 Hz, 12kw					
	One Year parts and labor warranty					
	• (2) Faucet bracket assembly					
	• (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer					
	• (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit)					
	• (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)		2	27139.86	54279.72	
ombination Oven	Combination Oven - Manufacturer/Model: Vulcan Model ABC7E-480 Full Size Electric Combi-Oven or pre approved equal. Furnish and	1				
	set in place per plans, elevations and manufacturer's specfications.					
	- Each unit to be 480V, 3 Phase, 60 Hz, 24k					
	- (4) stainless steel Grab-n-Go Racks with 151/2" x 31/4" cutout					
	design for easy access to pans.					
	- All stainless steel cavity, top, sides & fully insulated					
	- capacity of (7) racks for a total of (7) 18" x 26" or (14) 12" x 20" pans		1	23180.64	23180.64	
erving Counter - Cold Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	4				
	CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe					
	sneeze guard with glass overshelf and lights. 120V/1P/60hz		4	14267.01	57068.04	

Serving Counter - Hot Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	2				
	CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral					
	stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz					
			2	13984.72	27969.44	
ROLL-THRU HEATED CABINET	Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate	4				
	Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,					
	Refer to MEP for connections					
	• 1 yr service/labor, 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 208V, 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		4	16179.82	64719.28	
ROLL-THRU REFRIGERATOR	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate	6				
	Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls.					
	Refer to MEP for connections					
	• 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 120V , 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		6	17916.26	107497.56	
WORK TABLE, STAINLESS STEEL TOP, W/	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with rear mounted Pot Rack Furnish and set in	1				
POT RACK	place per plans, elevations and manufacturer's specifications					
	• Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf.					
	Provide table with one (1) pot rack to be rear-mounted to table					
	Provide One (1) #1 Edlund can opener and mount to table per drawing					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	3548.59	3548.59	
Work Table w/drawers and can opener	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table	1				
	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under					
	shelf.					
	Provide One (1) Edlund can opener and mount to table per drawing.					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	2626.91	2626.91	
Work Tables w/drawers	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table	4				
	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides					
			4	14267.01	57068.04	
HAND SINK	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal	2				
	Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with					
	hardware, stainless steel					
	Faucet, splash type, rigid gooseneck, with standard handles					
	Foot Pedal Valve					
	• Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts					
	• P Trap		2	1136.99	2273.98	

TWO (2) COMPARTMENT SINK	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.	1					
	Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.						
	• Sink to be 18" x 24" with 18" drainboards each side.						
	Wash sink compartment to be 11-1/2" deep.						
	• Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall						
	bracket.						
	Add-On-Faucet with 12" swing spout						
				1	4359.89	4359.89	
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	1					
ON FAUCET				1	402	402	
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	1	1				
					198.6	\$198.60	
THREE (3) COMPARTMENT SINK	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite or pre- approved alternate	1					
	Regaline Sink, 3-compartment, with left & right-hand drainboards, 24"						
	front-to-back x 24"W sink compartments, 14" deep, with 11"H						
	backsplash, stainless steel legs with welded front-to-rear & adjustable						
	left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14						
	gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF						
	(requires 2 faucets)						
	1 ea K-453 Control Bracket, 14" x 16" (each)						
	3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections						
	3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain			1	6183.88	6183.88	
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	1					
ON FAUCET				1	402	402	
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	1	1				
					198.6	\$198.60	
VENT HOOD - LED LIGHTS	Rated for 30,000 hours, 30x longer than a standard incandescent bulb	2					
	1350 lumens, 12 watt (75 watt equivalent)						
	Unbreakable polycarbonate enclosure						
	120 degree beam angle provides excellent light coverage						
	Safety shut off turns the light off at 275 degrees Fahrenheit; turns back on at 189 degrees Fahrenheit			2	96.49	192.98	
WALK-IN LED LIGHTS	Manufacturer: Sylvania SL74472LED6A19/F/850/10YV/RP2	6					
	400 Lumens; 6 watts; 11,000 hours; 120 volts; Cri 80			6	33.99	203.94	
REFRIGERATOR RACK, ROLL-IN	Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing	0	10				
	(nonadjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights,						
	(4) 5" platform swivel casters, NSF 8 ea Lifetime guarantee against rust & corrosion. Lifetime guarantee against worksmanship and						
	material defects.				1239.88	\$0.00	
						\$490 896 15	

\$490,896.15

IDEA Pharr					
Item	Description	Quantity			
			Price	Total Cost	Vendor notes

	T	1 -	1		
Convection Oven	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per	6			
	plans, elevations and manufacturer's specifications.				
	Provide Blodgett full size convection oven model Mark V (double) compartment.				
	• Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans.				
	• Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous				
	operation.				
	Unit to be electrically heated with three tubular heaters.				
	• Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload				
	protection.				
	• Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks.				
	• Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60				
	minute timer.				
	Equip units with all standard features available on these units.				
	Double-Deck				
	Provide all stainless steel 8" legs.				
	Provide vent connector.				
	Warranty; provide Five year limited oven door warranty.				
	One-year parts and labor warranty.				
	• Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total		6 13087.0	78522.06	
TILTING SKILLET BRAISING PAN, ELECTRIC	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans,	2			
	elevations and manufacturer's specifications				
	• Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer				
	Cover to be stainless steel and hinged with condensate ring				
	Power pan tilt, tilting console with provision for faucet				
	• Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition				
	• Each unit to be 480V, 3 phase, 60 Hz, 12kw				
	One Year parts and labor warranty				
	• (2) Faucet bracket assembly				
	• (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer				
	• (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit)				
	• (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)		2 22053.5	44107.06	
Combination Oven	Combination Oven - Manufacturer/Model: Vulcan Model ABC7E-480 Full Size Electric Combi-Oven or pre approved equal. Furnish and	1			
	set in place per plans, elevations and manufacturer's specfications.				
	- Each unit to be 480V, 3 Phase, 60 Hz, 24k				
	- (4) stainless steel Grab-n-Go Racks with 151/2" x 31/4" cutout				
	design for easy access to pans.				
	- All stainless steel cavity, top, sides & fully insulated				
	- capacity of (7) racks for a total of (7) 18" x 26" or (14) 12" x 20" pans		1 23180.6	23180.64	
Serving Counter - Cold Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	4			
	CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe				
	sneeze guard with glass overshelf and lights. 120V/1P/60hz		4 1426	57044	
Serving Counter - Hot Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	4			
	CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral				
	stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz				
			4 13984.7	72 55938.88	
ROLL-THRU HEATED CABINET	Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate	6	1		
	Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-				
	height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,				
	• Refer to MEP for connections				
	• 1 yr service/labor, 3 yr parts & warranty, standard				
	• Thermometer side: Door hinging to be determined				
	• Rear: Door hinging to be determined				
	• 208V, 1P, 60hz				
	• Provide New Age 4338 Roll-in Rack at each unit.		6 16179.8	97078.92	
	1	1		3.0.0.52	

DOLL TUDIL DEEDICEDATOR	Dell'Thur. Defice and a Cabinet. Translate Medal ADM 221 DUT FUG an area annual althought.				<u> </u>	
ROLL-THRU REFRIGERATOR	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate	6				
	Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls.					
	Refer to MEP for connections					
	• 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 120V , 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		6	17916.26	107497.56	
WORK TABLE, STAINLESS STEEL TOP, W/	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with rear mounted Pot Rack Furnish and set in	1				
POT RACK	place per plans, elevations and manufacturer's specifications					
	• Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf.					
	Provide table with one (1) pot rack to be rear-mounted to table					
	Provide One (1) #1 Edlund can opener and mount to table per drawing					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	3548.59	3548.59	
Work Table w/drawers and can opener	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table	1				
	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under					
	shelf.					
	Provide One (1) Edlund can opener and mount to table per drawing.					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	2626.91	2626.91	
Work Tables w/drawers	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table	3				
,	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		3	2069.28	6207.84	
HAND SINK	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal	3				
	Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with					
	hardware, stainless steel					
	• Faucet, splash type, rigid gooseneck, with standard handles					
	• Foot Pedal Valve					
	• Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts					
	• P Trap		3	3410.97	1136.99	
TWO (2) COMPARTMENT SINK	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.	0		3 120.57	1130.33	
TWO (2) CONTANTIVIZION SINK	Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.					
	• Sink to be 18" x 24" with 18" drainboards each side.					
	Wash sink compartment to be 11-1/2" deep.					
	• Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall					
	bracket.					
DDE DINICE EALICET ACCEMBLY MITH ADD	• Add-On-Faucet with 12" swing spout Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout		+			
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Fre-kinse Onic, o C/C backsplash mount, with spring action nexible gooseneck, wall pracket, Add-On-Faucet with 12 Swing spout	"				
ON FAUCET	Forcet Oll a/a heatenlash /well means to with 421 and a group layou be will a F7 to tall advisor 4/21 along the side of the si		+			
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	0				

THREE (3) COMPARTMENT SINK	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate	o				
	Regaline Sink, 3-compartment, with left & right-hand drainboards, 24"					
	front-to-back x 24"W sink compartments, 14" deep, with 11"H					
	backsplash, stainless steel legs with welded front-to-rear & adjustable					
	left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14					
	gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF					
	(requires 2 faucets)					
	1 ea K-453 Control Bracket, 14" x 16" (each)					
	3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections					
	3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain					
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	0				
ON FAUCET						
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	0				
VENT HOOD - LED LIGHTS	Rated for 30,000 hours, 30x longer than a standard incandescent bulb	2				
	1350 lumens, 12 watt (75 watt equivalent)					
	Unbreakable polycarbonate enclosure					
	120 degree beam angle provides excellent light coverage					
	Safety shut off turns the light off at 275 degrees Fahrenheit; turns back on at 189 degrees Fahrenheit		2	96.49	192.98	
WALK-IN LED LIGHTS	Manufacturer: Sylvania SL74472LED6A19/F/850/10YV/RP2	6				
	400 Lumens; 6 watts; 11,000 hours; 120 volts; Cri 80		(33.99	203.94	
REFRIGERATOR RACK, ROLL-IN	Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing	0				
	(nonadjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights,					
	(4) 5" platform swivel casters, NSF 8 ea Lifetime guarantee against rust & corrosion. Lifetime guarantee against worksmanship and					
	material defects.		12	1239.88	0	

\$ 477,286.37

IDEA Edinburg						
Item	Description	Quantity				
				Price	Total Cost	Vendor notes
Convection Oven	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per	6				
	plans, elevations and manufacturer's specifications.					
	• Provide Blodgett full size convection oven model Mark V (double) compartment.					
	• Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans.					
	• Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous					
	operation.					
	Unit to be electrically heated with three tubular heaters.					
	• Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload					
	protection.					
	• Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks.					
	• Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60					
	minute timer.					
	• Equip units with all standard features available on these units.					
	Double-Deck					
	• Provide all stainless steel 8" legs.					
	Provide vent connector.					
	Warranty; provide Five year limited oven door warranty.					
	One-year parts and labor warranty.					
	• Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total		6	13087.01	78522.06	

TILTING SKILLET BRAISING PAN, ELECTRIC	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans,	2				
	elevations and manufacturer's specifications					
	• Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer					
	Cover to be stainless steel and hinged with condensate ring					
	Power pan tilt, tilting console with provision for faucet					
	• Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition					
	• Each unit to be 480V, 3 phase, 60 Hz, 12kw					
	One Year parts and labor warranty					
	• (2) Faucet bracket assembly					
	• (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer					
	• (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit)					
	• (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)		2	27139.86	54279.72	
Combination Oven	Combination Oven - Manufacturer/Model: Vulcan Model ABC7E-480 Full Size Electric Combi-Oven or pre approved equal. Furnish and	1	_	27200.00	0.1270.72	
Combination Sven	set in place per plans, elevations and manufacturer's specifications.	1				
	- Each unit to be 480V, 3 Phase, 60 Hz, 24k					
	- (4) stainless steel Grab-n-Go Racks with 151/2" x 31/4" cutout					
	design for easy access to pans.					
	- All stainless steel cavity, top, sides & fully insulated			22400 64	22400 64	
	- capacity of (7) racks for a total of (7) 18" x 26" or (14) 12" x 20" pans		1	23180.64	23180.64	
Serving Counter - Cold Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	4				
	CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe					
	sneeze guard with glass overshelf and lights. 120V/1P/60hz		4	14261	57044	
Serving Counter - Hot Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	4				
	CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral					
	stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz					
			4	13984.72	55938.88	
ROLL-THRU HEATED CABINET	Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate	6				
	Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,					
	Refer to MEP for connections					
	• 1 yr service/labor, 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 208V, 1P, 60hz					
	• Provide New Age 4338 Roll-in Rack at each unit.		6	16179.82	97078.92	
ROLL-THRU REFRIGERATOR	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate	6		10173.82	37078.32	
ROLL-THRO REFRIGERATOR		В				
	Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls.					
	Refer to MEP for connections					
	• 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 120V , 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		6	17916.26	107497.56	
WORK TABLE, STAINLESS STEEL TOP, W/	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with rear mounted Pot Rack Furnish and set in	1				
POT RACK	place per plans, elevations and manufacturer's specifications					
	• Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf.					
	Provide table with one (1) pot rack to be rear-mounted to table					
	Provide One (1) #1 Edlund can opener and mount to table per drawing					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	3251.99	3251.99	
				0_01.00	0_01.00	

	<u></u>				
Work Table w/drawers and can opener	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table	1			
	Furnish and set in place per plans, elevations and manufacturer's specifications				
	• Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under				
	shelf.				
	• Provide One (1) Edlund can opener and mount to table per drawing.				
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)				
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)				
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1 2923.51	2923.51	
Work Tables w/drawers	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table	3			
	Furnish and set in place per plans, elevations and manufacturer's specifications				
	• Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs				
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)				
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)				
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		3 2069.28	6207.84	
HAND SINK	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal	3			
	Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with				
	hardware, stainless steel				
	• Faucet, splash type, rigid gooseneck, with standard handles				
	• Foot Pedal Valve				
	• Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts				
	• P Trap		3 1136.99	3410.97	
TWO (2) COMPARTMENT SINK	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.	0			
	Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.				
	• Sink to be 18" x 24" with 18" drainboards each side.				
	• Wash sink compartment to be 11-1/2" deep.				
	• Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall				
	bracket.				
	Add-On-Faucet with 12" swing spout				
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	0			
ON FAUCET					
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	0			
THREE (3) COMPARTMENT SINK	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate	0			
(-,	Regaline Sink, 3-compartment, with left & right-hand drainboards, 24"				
	front-to-back x 24"W sink compartments, 14" deep, with 11"H				
	backsplash, stainless steel legs with welded front-to-rear & adjustable				
	left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14				
	gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF				
	(requires 2 faucets)				
	1 ea K-453 Control Bracket, 14" x 16" (each)				
	3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections				
	3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain				
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	0			
ON FAUCET	and the same of the same spinish mount, with spinish action hexibic goodeneer, with bracket, Aud on radice with 12 swilling spout	Ĭ			
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	0			
VENT HOOD - LED LIGHTS	Rated for 30,000 hours, 30x longer than a standard incandescent bulb	2			
	1350 lumens, 12 watt (75 watt equivalent)				
	Unbreakable polycarbonate enclosure				
	120 degree beam angle provides excellent light coverage				
	Safety shut off turns the light off at 275 degrees Fahrenheit; turns back on at 189 degrees Fahrenheit		96.49	192.98	
WALK-IN LED LIGHTS	Manufacturer: Sylvania SL74472LED6A19/F/850/10YV/RP2	6			
	400 Lumens; 6 watts; 11,000 hours; 120 volts; Cri 80		6 33.99	203.94	

REFRIGERATOR RACK, ROLL-IN	Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing	0				
	(nonadjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights,					
	(4) 5" platform swivel casters, NSF 8 ea Lifetime guarantee against rust & corrosion. Lifetime guarantee against worksmanship and					
	material defects.		12	1239.88	0	

\$ 489,733.01

IDEA Brownsville						
Item	Description	Quantity				
		•		Price	Total Cost	Vendor notes
Convection Oven	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per	6	5			
	plans, elevations and manufacturer's specifications.					
	Provide Blodgett full size convection oven model Mark V (double) compartment.					
	• Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans.					
	• Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous					
	operation.					
	Unit to be electrically heated with three tubular heaters.					
	• Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload					
	protection.					
	• Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks.					
	• Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60					
	minute timer.					
	• Equip units with all standard features available on these units.					
	• Double-Deck					
	• Provide all stainless steel 8" legs.					
	Provide vent connector.					
	Warranty; provide Five year limited oven door warranty.					
	One-year parts and labor warranty.					
	• Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total			6 13087.0	78522.06	
TILTING SKILLET BRAISING PAN, ELECTRIC	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans,	2	2			
	elevations and manufacturer's specifications					
	• Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer					
	Cover to be stainless steel and hinged with condensate ring					
	Power pan tilt, tilting console with provision for faucet					
	• Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition					
	• Each unit to be 480V, 3 phase, 60 Hz, 12kw					
	One Year parts and labor warranty					
	• (2) Faucet bracket assembly					
	• (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer					
	• (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit)					
	• (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)			2 27139.8	54279.72	
Combination Oven	Combination Oven - Manufacturer/Model: Vulcan Model ABC7E-480 Full Size Electric Combi-Oven or pre approved equal. Furnish and	1				
	set in place per plans, elevations and manufacturer's specfications.					
	- Each unit to be 480V, 3 Phase, 60 Hz, 24k					
	- (4) stainless steel Grab-n-Go Racks with 151/2" x 31/4" cutout					
	design for easy access to pans.					
	- All stainless steel cavity, top, sides & fully insulated					
	- capacity of (7) racks for a total of (7) 18" x 26" or (14) 12" x 20" pans			1 23180.6	23180.64	
Serving Counter - Cold Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	C)			
	CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe					
	sneeze guard with glass overshelf and lights. 120V/1P/60hz			1		
Serving Counter - Hot Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	C)			
	CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral					
	stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz					

DOLL TUBLI USATED CABINIST	D. H. T. L. H. J. L. M. J. LANGON D. FUG.	1		I	
ROLL-THRU HEATED CABINET	Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate	4			
	Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-				
	height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,				
	Refer to MEP for connections				
	• 1 yr service/labor, 3 yr parts & warranty, standard				
	Thermometer side: Door hinging to be determined				
	Rear: Door hinging to be determined				
	• 208V, 1P, 60hz				
	Provide New Age 4338 Roll-in Rack at each unit.		4 16179.82	64719.28	
ROLL-THRU REFRIGERATOR	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate	4			
	Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-				
	height doors, INTELA-TRAUL™ microprocessor controls.				
	Refer to MEP for connections				
	• 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard				
	• Thermometer side: Door hinging to be determined				
	• Rear: Door hinging to be determined				
	• 120V , 1P, 60hz				
			4 17916.26	71665.04	
NAODIC TABLE STAINLESS STEEL TOD MAN	Provide New Age 4338 Roll-in Rack at each unit. Work Table w/ Bat Book - Many factories / Madel CounterCraft Lite Madel Brow Table with year mounted Bat Book Europish and act in	1	4 1/910.20	71005.04	
WORK TABLE, STAINLESS STEEL TOP, W/	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with rear mounted Pot Rack Furnish and set in	1			
POTRACK	place per plans, elevations and manufacturer's specifications				
	• Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf.				
	Provide table with one (1) pot rack to be rear-mounted to table				
	Provide One (1) #1 Edlund can opener and mount to table per drawing				
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)				
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)				
	• Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1 3548.59	3548.59	
Work Table w/drawers and can opener	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table	1			
	Furnish and set in place per plans, elevations and manufacturer's specifications				
	• Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under				
	shelf.				
	Provide One (1) Edlund can opener and mount to table per drawing.				
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)				
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)				
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1 2923.51	2923.51	
Work Tables w/drawers	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table	3			
	Furnish and set in place per plans, elevations and manufacturer's specifications				
	• Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs				
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)				
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)				
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		3 6207.84	6207.84	
HAND SINK	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal	2	3 0207.01	0207.01	
TIAND SINK	Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with	,			
	hardware, stainless steel	'			
	• Faucet, splash type, rigid gooseneck, with standard handles				
	• Foot Pedal Valve				
	• Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts		1425.00	2272.00	
TIMO (2) COMADADTA STUT COM	• P Trap	+ +	2 1136.99	2273.98	
TWO (2) COMPARTMENT SINK	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.	1			
	Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.				
	• Sink to be 18" x 24" with 18" drainboards each side.				
	Wash sink compartment to be 11-1/2" deep.				
	• Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall				
	bracket.				
	Add-On-Faucet with 12" swing spout		1 4151.07	4151.07	

PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	1				
ON FAUCET			1	402	402	
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	1				
			1	198.6	198.6	
THREE (3) COMPARTMENT SINK	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate	1				
	Regaline Sink, 3-compartment, with left & right-hand drainboards, 24"					
	front-to-back x 24"W sink compartments, 14" deep, with 11"H					
	backsplash, stainless steel legs with welded front-to-rear & adjustable					
	left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14					
	gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF					
	(requires 2 faucets)					
	1 ea K-453 Control Bracket, 14" x 16" (each)					
	3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections					
	3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain		1	6183.88	6183.88	
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	1				
ON FAUCET			1	402	402	
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	1				
			1	198.6	198.6	
VENT HOOD - LED LIGHTS	Rated for 30,000 hours, 30x longer than a standard incandescent bulb	2				
	1350 lumens, 12 watt (75 watt equivalent)					
	Unbreakable polycarbonate enclosure					
	120 degree beam angle provides excellent light coverage					
	Safety shut off turns the light off at 275 degrees Fahrenheit; turns back on at 189 degrees Fahrenheit		2	96.49	192.98	
WALK-IN LED LIGHTS	Manufacturer: Sylvania SL74472LED6A19/F/850/10YV/RP2	6				
	400 Lumens; 6 watts; 11,000 hours; 120 volts; Cri 80		6	33.99	203.94	
REFRIGERATOR RACK, ROLL-IN	Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing	0				
	(nonadjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights,					
	(4) 5" platform swivel casters, NSF 8 ea Lifetime guarantee against rust & corrosion. Lifetime guarantee against worksmanship and					
	material defects.		8	1239.88	o	

\$ 319,253.73

IDEA McAllen						
tem	Description	Quantity				
				Price	Total Cost	Vendor notes
Convection Oven	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per	6	5			
	plans, elevations and manufacturer's specifications.					
	Provide Blodgett full size convection oven model Mark V (double) compartment.					
	• Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans.					
	• Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous					
	operation.					
	Unit to be electrically heated with three tubular heaters.					
	• Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload					
	protection.					
	• Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks.					
	• Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60					
	minute timer.					
	• Equip units with all standard features available on these units.					
	Double-Deck					
	Provide all stainless steel 8" legs.					
	Provide vent connector.					
	Warranty; provide Five year limited oven door warranty.					
	One-year parts and labor warranty.					
	• Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total			6 13087.01	78522.06	

TILTING SKILLET BRAISING PAN, ELECTRIC	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans,	2				
	elevations and manufacturer's specifications					
	Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer					
	Cover to be stainless steel and hinged with condensate ring					
	Power pan tilt, tilting console with provision for faucet					
	• Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition					
	• Each unit to be 480V, 3 phase, 60 Hz, 12kw					
	One Year parts and labor warranty					
	• (2) Faucet bracket assembly					
	• (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer					
	• (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit)					
	• (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)		2	27139.86	54279.72	
Combi Over	Combination Oven - Manufacturer/Model: Vulcan Model ABC7E-480 Full Size Electric Combi-Oven or pre approved equal. Furnish and	1				
	set in place per plans, elevations and manufacturer's specfications.					
	- Each unit to be 480V, 3 Phase, 60 Hz, 24k					
	- (4) stainless steel Grab-n-Go Racks with 151/2" x 31/4" cutout					
	design for easy access to pans.					
	- All stainless steel cavity, top, sides & fully insulated					
	- capacity of (7) racks for a total of (7) 18" x 26" or (14) 12" x 20" pans		1	23180.64	23180.64	
Serving Counter - Cold Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	4	- 1	23180.04	23180.04	
Serving Counter - Cold Line	· ··	4				
	CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe			14261	F7044	
	sneeze guard with glass overshelf and lights. 120V/1P/60hz		4	14261	57044	
Serving Counter - Hot Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	4				
	CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral					
	stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz					
			4	13984.72	55938.88	
ROLL-THRU HEATED CABINET	Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate	6				
	Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,					
	Refer to MEP for connections					
	• 1 yr service/labor, 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 208V, 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		6	16179.82	97078.92	
ROLL-THRU REFRIGERATOR	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate	6				
	Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls.					
	Refer to MEP for connections					
	• 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 120V , 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		6	17916.26	107497.56	
WORK TABLE, STAINLESS STEEL TOP, W/	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with rear mounted Pot Rack Furnish and set in	1	<u> </u>	2.310.20	237.37.30	
POT RACK	place per plans, elevations and manufacturer's specifications	1				
	• Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf.					
	Provide table with one (1) pot rack to be rear-mounted to table					
	Provide One (1) #1 Edlund can opener and mount to table per drawing Printeged and archive true for an developing recognized and 20 lbs not as: ft. evenly distributed assignt) (assh)					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)		_	2254 02	2254 82	
	• Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	3251.99	3251.99	

Work Table w/drawers and can opener	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table	1			
	Furnish and set in place per plans, elevations and manufacturer's specifications				
	• Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under				
	shelf.				
	Provide One (1) Edlund can opener and mount to table per drawing.				
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)				
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)				
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1 2923.51	2923.51	
Work Tables w/drawers	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table	3			
	Furnish and set in place per plans, elevations and manufacturer's specifications				
	• Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs				
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)				
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)				
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		3 2069.28	6207.84	
HAND SINK	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal	3			
	Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with				
	hardware, stainless steel				
	Faucet, splash type, rigid gooseneck, with standard handles				
	Foot Pedal Valve				
	• Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts				
	• P Trap		3 1136.99	3410.97	
TWO (2) COMPARTMENT SINK	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.	0			
	Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.				
	• Sink to be 18" x 24" with 18" drainboards each side.				
	• Wash sink compartment to be 11-1/2" deep.				
	• Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall				
	bracket.				
	Add-On-Faucet with 12" swing spout				
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	0			
ON FAUCET					
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	0			
THREE (3) COMPARTMENT SINK	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate	0			
	Regaline Sink, 3-compartment, with left & right-hand drainboards, 24"				
	front-to-back x 24"W sink compartments, 14" deep, with 11"H				
	backsplash, stainless steel legs with welded front-to-rear & adjustable				
	left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14				
	gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF				
	(requires 2 faucets)				
	1 ea K-453 Control Bracket, 14" x 16" (each)				
	3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections				
	3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain				
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	0			
ON FAUCET	The families of the buckey lustriff with spring detail nextisic goodeneek, wall brucket, Add on rudeet with 12 Swing spout	Ĭ			
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	0			
VENT HOOD - LED LIGHTS	Rated for 30,000 hours, 30x longer than a standard incandescent bulb	2			
	1350 lumens, 12 watt (75 watt equivalent)				
	Unbreakable polycarbonate enclosure				
	120 degree beam angle provides excellent light coverage				
	Safety shut off turns the light off at 275 degrees Fahrenheit; turns back on at 189 degrees Fahrenheit		96.49	192.98	
WALK-IN LED LIGHTS	Manufacturer: Sylvania SL74472LED6A19/F/850/10YV/RP2	6			
	400 Lumens; 6 watts; 11,000 hours; 120 volts; Cri 80		6 33.99	203.94	

REFRIGERATOR RACK, ROLL-IN	Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing	0				
	(nonadjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights,					
	(4) 5" platform swivel casters, NSF 8 ea Lifetime guarantee against rust & corrosion. Lifetime guarantee against worksmanship and					
	material defects.		12	1239.88	0	
	·	-		•	4	

\$ 489,733.01

IDEA Carver						
tem	Description	Quantity				
				Price	Total Cost	Vendor notes
Convection Oven	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per	6				
	plans, elevations and manufacturer's specifications.					
	Provide Blodgett full size convection oven model Mark V (double) compartment.					
	• Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans.					
	• Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous					
	operation.					
	• Unit to be electrically heated with three tubular heaters.					
	• Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload					
	protection.					
	• Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks.					
	• Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60					
	minute timer.					
	• Equip units with all standard features available on these units.					
	Double-Deck					
	• Provide all stainless steel 8" legs.					
	Provide vent connector.					
	Warranty; provide Five year limited oven door warranty.					
	One-year parts and labor warranty.					
	Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total		6	13087.01	78522.06	
TILTING SKILLET BRAISING PAN, ELECTRIC	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans,	1				
	elevations and manufacturer's specifications					
	• Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer					
	Cover to be stainless steel and hinged with condensate ring					
	Power pan tilt, tilting console with provision for faucet					
	• Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition					
	• Each unit to be 480V, 3 phase, 60 Hz, 12kw					
	One Year parts and labor warranty					
	• (2) Faucet bracket assembly					
	• (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer					
	• (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit)					
	• (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)		1	27139.86	27139.86	
Combination Oven	Combination Oven - Manufacturer/Model: Vulcan Model ABC7E-480 Full Size Electric Combi-Oven or pre approved equal. Furnish and	1				
	set in place per plans, elevations and manufacturer's specfications.					
	- Each unit to be 480V, 3 Phase, 60 Hz, 24k					
	- (4) stainless steel Grab-n-Go Racks with 151/2" x 31/4" cutout					
	design for easy access to pans.					
	- All stainless steel cavity, top, sides & fully insulated					
	- capacity of (7) racks for a total of (7) 18" x 26" or (14) 12" x 20" pans		1	23180.64	23180.64	
erving Counter - Cold Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	2				
	CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe					
	sneeze guard with glass overshelf and lights. 120V/1P/60hz		2	14261	28522	
erving Counter - Hot Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	2				
	CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral					
	stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz					
			2	13984.72	27969.44	

	I- w					
ROLL-THRU HEATED CABINET	Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate	2				
	Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,					
	Refer to MEP for connections					
	• 1 yr service/labor, 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 208V, 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		2	16179.82	32359.64	
ROLL-THRU REFRIGERATOR	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate	2				
	Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls.					
	Refer to MEP for connections					
	• 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 120V , 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		2	17916.26	35832.52	
WORK TABLE, STAINLESS STEEL TOP, W/	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with rear mounted Pot Rack Furnish and set in	1				
POT RACK	place per plans, elevations and manufacturer's specifications					
	• Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf.					
	Provide table with one (1) pot rack to be rear-mounted to table					
	Provide One (1) #1 Edlund can opener and mount to table per drawing					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	2637.07	2637.07	
Work Table w/drawers and can opener	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table	1				
, , , , , , , , , , , , , , , , , , , ,	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under					
	shelf.					
	Provide One (1) Edlund can opener and mount to table per drawing.					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	2626.91	2626.91	
Work Tables w/drawers	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table	3		2020.51	2020.51	
Work Tables Wy drawers	Furnish and set in place per plans, elevations and manufacturer's specifications	3				
	Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs					
	Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		2	2069.28	6207.84	
HAND SINK	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal	2	3	2009.28	0207.84	
INAIND SINK		2				
	Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with					
	hardware, stainless steel					
	• Faucet, splash type, rigid gooseneck, with standard handles					
	• Foot Pedal Valve					
	• Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts			4436.00	2272.00	
TIME (2) CONTRACTOR STATES	• P Trap		2	1136.99	2273.98	
TWO (2) COMPARTMENT SINK	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.	0				
	Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.					
	• Sink to be 18" x 24" with 18" drainboards each side.					
	Wash sink compartment to be 11-1/2" deep.					
	• Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall					
	bracket.					
1	Add-On-Faucet with 12" swing spout		ı			

PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	0				
ON FAUCET						
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	0				
THREE (3) COMPARTMENT SINK	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate	1				
	Regaline Sink, 3-compartment, with left & right-hand drainboards, 24"					
	front-to-back x 24"W sink compartments, 14" deep, with 11"H					
	backsplash, stainless steel legs with welded front-to-rear & adjustable					
	left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14					
	gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF					
	(requires 2 faucets)					
	1 ea K-453 Control Bracket, 14" x 16" (each)					
	3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections					
	3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain		1	6183.88	6183.88	
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	1				
ON FAUCET			1	402	402	
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	1				
			1	255	255	
VENT HOOD - LED LIGHTS	Rated for 30,000 hours, 30x longer than a standard incandescent bulb	2				
	1350 lumens, 12 watt (75 watt equivalent)					
	Unbreakable polycarbonate enclosure					
	120 degree beam angle provides excellent light coverage					
	Safety shut off turns the light off at 275 degrees Fahrenheit; turns back on at 189 degrees Fahrenheit		2	96.49	192.98	
WALK-IN LED LIGHTS	Manufacturer: Sylvania SL74472LED6A19/F/850/10YV/RP2	6				
	400 Lumens; 6 watts; 11,000 hours; 120 volts; Cri 80		6	33.99	203.94	
REFRIGERATOR RACK, ROLL-IN	Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing	6				
	(nonadjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights,					
	(4) 5" platform swivel casters, NSF 8 ea Lifetime guarantee against rust & corrosion. Lifetime guarantee against worksmanship and					
	material defects.		10	1239.88	7439.28	

\$ 281,949.04

IDEA South Flores						
tem	Description	Quantity				
				Price	Total Cost	Vendor notes
onvection Oven	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per	6				
	plans, elevations and manufacturer's specifications.					
	Provide Blodgett full size convection oven model Mark V (double) compartment.					
	• Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans.					
	• Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous					
	operation.					
	Unit to be electrically heated with three tubular heaters.					
	• Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload					
	protection.					
	• Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks.					
	• Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60					
	minute timer.					
	Equip units with all standard features available on these units.					
	Double-Deck					
	Provide all stainless steel 8" legs.					
	Provide vent connector.					
	Warranty; provide Five year limited oven door warranty.					
	One-year parts and labor warranty.					
	• Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total		6	13087.01	78522.06	

TILTING SKILLET BRAISING PAN, ELECTRIC	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans,	2				
	elevations and manufacturer's specifications					
	• Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer					
	Cover to be stainless steel and hinged with condensate ring					
	Power pan tilt, tilting console with provision for faucet					
	• Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition					
	• Each unit to be 480V, 3 phase, 60 Hz, 12kw					
	One Year parts and labor warranty					
	• (2) Faucet bracket assembly					
	• (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer					
	• (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit)					
	• (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)		2	27139.86	54279.72	
Combination Oven	Combination Oven - Manufacturer/Model: Vulcan Model ABC7E-480 Full Size Electric Combi-Oven or pre approved equal. Furnish and	1	_			
Combination Sven	set in place per plans, elevations and manufacturer's specifications.	-				
	- Each unit to be 480V, 3 Phase, 60 Hz, 24k					
	- (4) stainless steel Grab-n-Go Racks with 151/2" x 31/4" cutout					
	design for easy access to pans.					
	- All stainless steel cavity, top, sides & fully insulated			22400.64	22400 64	
	- capacity of (7) racks for a total of (7) 18" x 26" or (14) 12" x 20" pans		1	23180.64	23180.64	
Serving Counter - Cold Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	0				
	CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe					
	sneeze guard with glass overshelf and lights. 120V/1P/60hz					
Serving Counter - Hot Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	0				
	CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral					
	stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz					
ROLL-THRU HEATED CABINET	Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate	4				
	Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,					
	Refer to MEP for connections					
	• 1 yr service/labor, 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 208V, 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		4	16179.82	64719.28	
ROLL-THRU REFRIGERATOR	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate	4				
	Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls.					
	Refer to MEP for connections					
	• 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard					
	• Thermometer side: Door hinging to be determined					
	• Rear: Door hinging to be determined					
	• 120V , 1P, 60hz					
	• Provide New Age 4338 Roll-in Rack at each unit.		4	17916.26	71665.04	
WORK TABLE, STAINLESS STEEL TOP, W/	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with rear mounted Pot Rack Furnish and set in	2	7	1/310.20	7 1003.04	
POT RACK	place per plans, elevations and manufacturer's specifications	ا				
TOT NACK						
	• Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf.					
	Provide table with one (1) pot rack to be rear-mounted to table					
	Provide One (1) #1 Edlund can opener and mount to table per drawing					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		3	2637.07	7911.21	

Waste Table /duantum and annual annual	Mark Table wilders and are arranged Mark factors (Mandal CounterCoeff Lite Mandal Days Table	4				
Work Table w/drawers and can opener	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table	1				
	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under					
	shelf.					
	Provide One (1) Edlund can opener and mount to table per drawing.					
	Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	2923.51	2923.51	
Work Tables w/drawers	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table	1				
	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	2069.28	2069.28	
HAND SINK	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal	2				
	Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with					
	hardware, stainless steel					
	Faucet, splash type, rigid gooseneck, with standard handles					
	Foot Pedal Valve					
	• Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts					
	• P Trap		2	1136.99	2273.98	
TWO (2) COMPARTMENT SINK	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.	1				
	Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.					
	• Sink to be 18" x 24" with 18" drainboards each side.					
	• Wash sink compartment to be 11-1/2" deep.					
	• Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall					
	bracket.					
	• Add-On-Faucet with 12" swing spout		1	4359.89	4359.89	
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	1			1000100	
ON FAUCET	grand of the state of the grand		1	402	402	
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	1				
			1	510	510	
THREE (3) COMPARTMENT SINK	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate	1				
	Regaline Sink, 3-compartment, with left & right-hand drainboards, 24"					
	front-to-back x 24"W sink compartments, 14" deep, with 11"H					
	backsplash, stainless steel legs with welded front-to-rear & adjustable					
	left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14					
	gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF					
	(requires 2 faucets)					
	1 ea K-453 Control Bracket, 14" x 16" (each)					
	3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections					
	3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain		1	6183.88	6183.88	
PRE-RINSE FAUCET ASSEMBLY, WITH ADD	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	1				
ON FAUCET			1	402	402	
		1				
IWALL / SPLASH MOUNT FAUCET	Faucet 8" c/c hacksplash/wall mount, with 12" swing spout, lever handles, F7-Install adapters, 1/2" close elhows, stainless steel, NSF					
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF		1	510	510	
WALL / SPLASH MOUNT FAUCET VENT HOOD - LED LIGHTS	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF Rated for 30,000 hours, 30x longer than a standard incandescent bulb	2	1	510	510	
·		2	1	510	510	
·	Rated for 30,000 hours, 30x longer than a standard incandescent bulb	2	1	510	510	
·	Rated for 30,000 hours, 30x longer than a standard incandescent bulb 1350 lumens, 12 watt (75 watt equivalent)	2	1	510	510	
·	Rated for 30,000 hours, 30x longer than a standard incandescent bulb 1350 lumens, 12 watt (75 watt equivalent) Unbreakable polycarbonate enclosure	2	2	510 96.49	192.98	
·	Rated for 30,000 hours, 30x longer than a standard incandescent bulb 1350 lumens, 12 watt (75 watt equivalent) Unbreakable polycarbonate enclosure 120 degree beam angle provides excellent light coverage	2	2			

REFRIGERATOR RACK, ROLL-IN	Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing	8				
	(nonadjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights,					
	(4) 5" platform swivel casters, NSF 8 ea Lifetime guarantee against rust & corrosion. Lifetime guarantee against worksmanship and					
	material defects.		16	1239.88	9919.04	
•		-	-		4 222 222 45	•

\$ 330,228.45

IDEA Montopolis						
Item	Description	Quantity				
				Price	Total Cost	Vendor notes
Convection Oven	Convection Oven - Manufacturer/Model: Blodgett Mark V. / Vulcan Model VC44ED or preapproved equal Furnish and set in place per	2				
	plans, elevations and manufacturer's specifications.					
	Provide Blodgett full size convection oven model Mark V (double) compartment.					
	• Provide all stainless steel compartments, that accept five 18" x 26" standard full size bake pans.					
	• Doors shall be stainless steel, equipped with dual pane thermal glass windows, with single porcelain handle and simultaneous					
	operation.					
	Unit to be electrically heated with three tubular heaters.					
	• Air in baking chamber distributed by single inlet blower wheel powered by a two- speed, 1/3 HP motor with thermal overload					
	protection.					
	• Each chamber shall be fitted with four commercial lamps and five chrome plated removable racks.					
	• Control panel shall be recessed with Cook/Cool Down mode selector, solid stated digital thermostat (200- 500 degrees) with 60					
	minute timer.					
	Equip units with all standard features available on these units.					
	Double-Deck					
	Provide all stainless steel 8" legs.					
	Provide vent connector.					
	Warranty; provide Five year limited oven door warranty.					
	One-year parts and labor warranty.					
	• Power; 480v, 3phase, 60Hz, 12.5Kw each, 25 kw total		2	13087.01	26174.02	
TILTING SKILLET BRAISING PAN, ELECTRIC	Tilting Skillet- Manufacturer/Model: Blodgett BLP-40E / Vulcan Model VE 40 or pre-approved equal Furnish and set in place per plans,	2				
	elevations and manufacturer's specifications					
	• Unit shall have stainless steel tube frame construction with rear flanged feet, stainless steel pan with pour lip strainer					
	Cover to be stainless steel and hinged with condensate ring					
	Power pan tilt, tilting console with provision for faucet					
	• Temperature range 160 electronic ignition F with range to 450 F with thermostatic temperature control and electronic ignition					
	• Each unit to be 480V, 3 phase, 60 Hz, 12kw					
	One Year parts and labor warranty					
	• (2) Faucet bracket assembly					
	• (2) Double pantry wash down hose with 16" add-on faucet with backflow preventer					
	• (2) Steaming Pan insert rack to hold 12"x20" pan (Qty. 3 per unit)					
	• (2) Stainless steel perforated boiling basket (12"x20"x6"D) with handles (Qty. 3 per unit)		2	27139.86	54279.72	
Combination Oven	Combination Oven - Manufacturer/Model: Vulcan Model ABC7E-480 Full Size Electric Combi-Oven or pre approved equal. Furnish and	0				
	set in place per plans, elevations and manufacturer's specfications.					
	- Each unit to be 480V, 3 Phase, 60 Hz, 24k					
	- (4) stainless steel Grab-n-Go Racks with 151/2" x 31/4" cutout					
	design for easy access to pans.					
	- All stainless steel cavity, top, sides & fully insulated					
	- capacity of (7) racks for a total of (7) 18" x 26" or (14) 12" x 20" pans					
Serving Counter - Cold Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	2				
	CounterCraft Modular Recessed Frost Unit, Quantity: Two (2), with FTB 2. Provide counter with cord and plug, with Adjustable Deluxe					
	sneeze guard with glass overshelf and lights. 120V/1P/60hz		2	14261	. 28522	
Serving Counter - Hot Line	Serving Counter - Countercraft Model SERVING COUNTER or pre-approved alternate	2				
	CounterCraft Modular Hot Food Unit, Quantity: Two (2), with Hatco GRSBF-36-S Built-in Heated Shelf. Provide counter with integral					
	stainless steel cutting surface, cord and plug, with Adjustable Deluxe sneeze guard and lights. 208V/1P/60hz 120V/1P/60hz					
] 2	13984.72	27969.44	

	T					
ROLL-THRU HEATED CABINET	Roll-Thru Heated Cabinet - Traulsen Model AIH132LP-FHS or pre-approved alternate	3				
	Spec-Line Heated Cabinet, Roll-Thru, self-contained, stainless steel exterior, aluminum interior, standard depth cabinet, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls, 6" adjustable s/s legs, NSF,					
	Refer to MEP for connections					
	• 1 yr service/labor, 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 208V, 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		3	16179.82	48539.46	
ROLL-THRU REFRIGERATOR	Roll-Thru Refrigerator Cabinet - Traulsen Model ARI132LPUT-FHS or pre-approved alternate	2				
	Spec-Line Refrigerator, Roll-Thru, self-contained refrigeration, stainless steel exterior, aluminum interior, standard depth, wide full-					
	height doors, INTELA-TRAUL™ microprocessor controls.					
	Refer to MEP for connections					
	• 1 yr service/labor, 5 yr compressor & 3 yr parts & warranty, standard					
	Thermometer side: Door hinging to be determined					
	Rear: Door hinging to be determined					
	• 120V , 1P, 60hz					
	Provide New Age 4338 Roll-in Rack at each unit.		2	17916.26	35832.52	
WORK TABLE, STAINLESS STEEL TOP, W/	Work Table w/ Pot Rack - Manufacturer/Model: CounterCraft Lite Model Prep Table with rear mounted Pot Rack Furnish and set in	3				
POT RACK	place per plans, elevations and manufacturer's specifications					
	• Work table, 30" wide top flat top, constructed of 14-gauge stainless steel with stainless steel legs, drawer and under shelf.					
	Provide table with one (1) pot rack to be rear-mounted to table					
	Provide One (1) #1 Edlund can opener and mount to table per drawing					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• Deluxe Drawer, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		3	2821.41	8464.23	
Work Table w/drawers and can opener	Work Table w/drawers and can opener - Manufacturer/Model: CounterCraft Lite Model Prep Table	1				
	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 36" x 72" wide top flat top, constructed of 14-gauge stainless steel with 8" locking casters, Three (3) drawer and under					
	shelf.					
	Provide One (1) Edlund can opener and mount to table per drawing.					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	2626.91	2626.91	
Work Tables w/drawers	Work Table w/drawers- Manufacturer/Model: CounterCraft Lite Model Prep Table	1				
·	Furnish and set in place per plans, elevations and manufacturer's specifications					
	• Work table, 30" 36" wide top flat top, 72" long, constructed of 14-gauge stainless steel with stainless steel legs					
	• Reinforced understructure for undershelves (maximum recommended load 30 lbs per sq. ft. evenly distributed weight) (each)					
	• 16 gauge 304 series stainless steel undershelf upgrade (per linear foot)					
	• 2 Deluxe Drawers, 15"W x 20"D x 5" deep drawer pan insert, stainless steel, with drawer slides		1	2069.28	2069.28	
HAND SINK	Hand Sink - IMC/Teddy Model CSW-2S or pre-approved equal	0				
	Hand Sink, wall mounted, with (2) holes for splash-mount faucet, integral backsplash, 6" apron, includes mounting bracket and clip with					
	hardware, stainless steel					
	• Faucet, splash type, rigid gooseneck, with standard handles					
	• Foot Pedal Valve					
	• Twist Waste Valve with Overflow, 1-1/2" waste outlet, cast bronze, stainless steel strainer, nickel-plated wearing parts					
	• P Trap					
TWO (2) COMPARTMENT SINK	Manufacturer/Model: CounterCraft Lite Model 2-COMPARTMENT SINK or pre- approved alternate.	0				
, ,	Two Compartment Sink - CounterCraft Lite Custom Fabricated 2-Compartment Sink, 72" in length.					
	• Sink to be 18" x 24" with 18" drainboards each side.					
	• Wash sink compartment to be 11-1/2" deep.					
	• Fisher Model 34460 or pre-approved alternate; Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall					
	bracket.					
	• Add-On-Faucet with 12" swing spout					
L	on acout man 12 on mg spoot	<u>. </u>				

PRE-RINSE FAUCET ASSEMBLY, WITH ADD ON FAUCET	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	0				
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	0				
THREE (3) COMPARTMENT SINK	3 Compartment Sink - Manufacturer/Model: CounterCraft Lite Model 3-COMPARTMENT SINK or pre- approved alternate Regaline Sink, 3-compartment, with left & right-hand drainboards, 24" front-to-back x 24"W sink compartments, 14" deep, with 11"H backsplash, stainless steel legs with welded front-to-rear & adjustable left-to-right cross rails, 36" drainboards, 1" adjustable bullet feet, 14 gauge 304 series stainless steel, overall 31" F/B x 151" L/R, NSF (requires 2 faucets) 1 ea K-453 Control Bracket, 14" x 16" (each) 3 ea K-5 Drain, twist operated, 2" NPT & 1-1/2" IPS outlet connections 3 ea K-4 Support Bracket, for lever waste drain handle, (1) support required for each lever drain	0				
PRE-RINSE FAUCET ASSEMBLY, WITH ADD ON FAUCET	Pre-Rinse Unit, 8" c/c backsplash mount, with spring action flexible gooseneck, wall bracket, Add-On-Faucet with 12" swing spout	0				
WALL / SPLASH MOUNT FAUCET	Faucet, 8" c/c backsplash/wall mount, with 12" swing spout, lever handles, EZ-Install adapters, 1/2" close elbows, stainless steel, NSF	0				
VENT HOOD - LED LIGHTS	Rated for 30,000 hours, 30x longer than a standard incandescent bulb 1350 lumens, 12 watt (75 watt equivalent) Unbreakable polycarbonate enclosure 120 degree beam angle provides excellent light coverage Safety shut off turns the light off at 275 degrees Fahrenheit; turns back on at 189 degrees Fahrenheit	2		2 96.	19 192.98	
WALK-IN LED LIGHTS	Manufacturer: Sylvania SL74472LED6A19/F/850/10YV/RP2 400 Lumens; 6 watts; 11,000 hours; 120 volts; Cri 80	6		6 33.9	99 203.94	
REFRIGERATOR RACK, ROLL-IN	Lifetime Series Roll-In Bun Pan Rack, heavy duty, aluminum, 64"H, (18) wide-angle runners are 1-1/2" x 3-1/4" x .100 with 3" spacing (nonadjustable), extruded aluminum guides for 12 x 20 to 18 x 26 pans, fully welded 1-1/2"x1-3/4" x .07" smooth wall D-tube uprights, (4) 5" platform swivel casters, NSF 8 ea Lifetime guarantee against rust & corrosion. Lifetime guarantee against worksmanship and material defects.	8	1	3 1239.	9919.04 \$ 244,793.54	

Buy Out (Optional)

Estimated Quantity	Description	Unit Buy Out
		price
44	Convection Oven	
15	TILTING SKILLET BRAISING PAN, ELECTRIC	
7	Combi Over	
20	Serving Counter - Cold Line	
18	Serving Counter - Hot Line	
35	ROLL-THRU HEATED CABINET	
36	ROLL-THRU REFRIGERATOR	
12	WORK TABLE, STAINLESS STEEL TOP, W/ POT RACK	
8	Work Table w/drawers and can opener	
21	Work Tables w/drawers	
17	HAND SINK	
3	TWO (2) COMPARTMENT SINK	
3	PRE-RINSE FAUCET ASSEMBLY, WITH ADD ON FAUCET	
3	WALL / SPLASH MOUNT FAUCET	
4	THREE (3) COMPARTMENT SINK	
4	PRE-RINSE FAUCET ASSEMBLY, WITH ADD ON FAUCET	
4	WALL / SPLASH MOUNT FAUCET	
22	REFRIGERATOR RACK, ROLL-IN	